

Product Description

A professional quality, interior, heavy-bodied latex wall primer. Designed to prime and surface interior wallboard. Good for commercial application.

Performance Features

- Uniforms Substrate
- Low Odor and VOC
- High Solids

Compliance & Certification

- ✓ Meets Green Seal GS-11 VOC Limits
- ✓ Meets LEED EQ Credit 4.2 VOC Limits
- ✓ Meets CARB VOC Limits
- ✓ Meets SCAQMD VOC Limits
- ✓ Meets National AIM VOC Limits

Product Specifications

Resin Type:	Vinyl Acrylic
Color Range:	Off White
Drying Time:	To touch: 1 Hour
(75° F. & 50% R.H.)	To recoat: 4 hours.
Practical coverage:	Approx. 150 - 200 sq ft/gallon
Recommended Dry Film Thickness:	3-5 mills
Weight per Gallon:	13.1 lbs. ± 0.25 lbs.
Solids by Weight:	64% ± 2%
Solids by Volume:	44% ± 2%
Sizes:	Five gallons
V.O.C.	<40 Grams per liter
Clean-Up:	Water

09 90 00 PAINTING AND COATING

Surface Preparation

General:

All surfaces must be cured, firm, dry and cleaned free of loose paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces*.

*See warning for existing leaded paint under Precautions.

System Recommendations

Masonry:

PRIMER: 123-102 Kel-Pro heavy Bodied Latex Wall Primer
FINISH: Appropriate Kelly-Moore finish.

Application: Brush, Roll, or Spray

Brush: Use synthetic bristle brush.

Roller: Use 1/4 – 3/4 inch nap roller cover depending on surface profile.

Spray: Airless sprayer use .015 to .017 orifice tip. For conventional or HVLP sprayers please consult sprayer manual for waterborne primers.

Do not apply when material, air, and/or surface temperature is below 50°F or above 90° F. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks. Do not allow material to pond on concrete floors.

Store at room temperature. Keep from freezing.

Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

Continued Next Page

123-102 KEL-PRO (cont.)

Precautions

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION.

KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.