

1. Identification

Product identifier 1240 AcryShield Flat Stock Colors

Other means of identification None.

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Kelly-Moore Paint Co., Inc.
Address 987 Commercial St., San Carlos, CA 94070
Telephone 1-800-874-4436
E-mail TAlvarez@kellymoore.com
Contact person Tiffany Alvarez Gonda
Emergency phone number CHEMTREC: 1-800-424-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of causing cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information This product contains Diphenyl Ketone at less than 0.2% which is suspected of causing cancer (See Section 11).

3. Composition/information on ingredients

Mixtures

| Chemical name | CAS number | % |
|------------------|------------|-------|
| Titanium dioxide | 13463-67-7 | < 21 |
| Diphenyl ketone | 119-61-9 | < 0.2 |

All concentrations are in percent by weight (kg) unless ingredient is a gas. Gas concentrations are in percent by volume (l).

4. First-aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Get medical attention if any discomfort continues.

Skin contact Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. Get medical attention if irritation persists after washing.

| | |
|---|---|
| Eye contact | Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. Get medical attention if symptoms persist. |
| Ingestion | Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions. |
| Most important symptoms/effects, acute and delayed | Direct contact with eyes may cause temporary irritation. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | If exposed or concerned: get medical attention/advice. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Extinguish with foam, carbon dioxide, dry powder or water fog. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | No unusual fire or explosion hazards noted. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Avoid inhalation of vapors and contact with skin and eyes. Wear appropriate personal protective equipment (See Section 8). |
| Methods and materials for containment and cleaning up | This product is moderately soluble in water. Should not be released into the environment. Large Spills: Absorb in vermiculite, dry sand or earth and place into containers. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| | |
|---|--|
| Precautions for safe handling | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices. |
| Conditions for safe storage, including any incompatibilities | Store locked up. Store away from incompatible materials (see Section 10 of the SDS). Store in tightly closed original container in a dry, cool and well-ventilated place. |

8. Exposure controls/personal protection

Occupational exposure limits

US. Workplace Environmental Exposure Level (WEEL) Guides

| Components | Type | Value | Form |
|----------------------------------|------|-----------------------|----------|
| Diphenyl ketone (CAS 119-61-9) | TWA | 0.5 mg/m ³ | |
| Propane -1,2 -diol (CAS 57-55-6) | TWA | 10 mg/m ³ | Aerosol. |

| | |
|--|---|
| Biological limit values | No biological exposure limits noted for the ingredient(s). |
| Appropriate engineering controls | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. |
| Individual protection measures, such as personal protective equipment | |
| Eye/face protection | Use safety glasses, goggles, or face shield to protect eyes. |
| Skin protection | |
| Hand protection | Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. |
| Other | Wear suitable protective clothing. |
| Respiratory protection | Use NIOSH certified, air purifying respirators with N-, P-, or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. protection provided by air-purifying respirators is limited. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR 1910.134. Consult a qualified industrial hygienist or Safety Professional for respirator selection guidance. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

| | |
|---|--------------------------------|
| Appearance | Milky white to colored liquid. |
| Physical state | Liquid. |
| Form | Liquid. |
| Color | Various. |
| Odor | Slightly ammoniacal. |
| Odor threshold | Not available. |
| pH | 7 - 10 |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | Not available. |
| Flash point | Not available. |
| Evaporation rate | < 1 (n-BuAc=1) |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | Not available. |
| Vapor density | > 1 (Air=1) |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Moderately soluble |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Explosive properties | Not explosive. |

Oxidizing properties Not oxidizing.
VOC 46.25 - 49.15 g/L

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability Material is stable under normal conditions.
Possibility of hazardous reactions Will not occur.
Conditions to avoid Contact with incompatible materials.
Incompatible materials Strong oxidizing agents. Strong acids.
Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.
Skin contact Prolonged or repeated contact may dry skin and cause irritation.
Eye contact Direct contact with eyes may cause temporary irritation.
Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Exposure may cause temporary irritation, redness, or discomfort.

Information on toxicological effects

Acute toxicity Ingestion may cause irritation and malaise. In high concentrations, vapors and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.

Skin corrosion/irritation Prolonged or repeated contact may dry skin and cause irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.
Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity The product contains a small amount of a substance that is suspected of causing cancer. Inhalation of carbon black or titanium dioxide dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

| | |
|--|---|
| Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2) | 3 Not classifiable as to carcinogenicity to humans. |
| Carbon black (CAS 1333-86-4) | 2B Possibly carcinogenic to humans. |
| Diphenyl ketone (CAS 119-61-9) | 2B Possibly carcinogenic to humans. |
| Iron oxide (CAS 1309-37-1) | 3 Not classifiable as to carcinogenicity to humans. |
| Silicon dioxide, crystalline silica-free (CAS 7631-86-9) | 3 Not classifiable as to carcinogenicity to humans. |
| Talc (CAS 14807-96-6) | 3 Not classifiable as to carcinogenicity to humans. |
| Titanium dioxide (CAS 13463-67-7) | 2B Possibly carcinogenic to humans. |

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged or repeated contact may dry skin and cause dermatitis.

Further information Components of the product may be absorbed into the body through the skin.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil The product is water soluble and may spread in water systems.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose in accordance with applicable federal, state, and local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Diphenyl ketone (CAS 119-61-9) 0.1 % One-Time Export Notification only.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Copper (CAS 7440-50-8) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|---------------|------------|----------|
| Copper | 7440-50-8 | < 4 |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)

Carbon black (CAS 1333-86-4)

Copper (CAS 7440-50-8)

Iron oxide (CAS 1309-37-1)

Kaolin (CAS 1332-58-7)

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Talc (CAS 14807-96-6)

Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

3-Iodo-2-propynyl butyl carbamate (CAS 55406-53-6)

Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)

Carbon black (CAS 1333-86-4)

Copper (CAS 7440-50-8)

Iron oxide (CAS 1309-37-1)

Kaolin (CAS 1332-58-7)

Propane -1,2 -diol (CAS 57-55-6)

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Talc (CAS 14807-96-6)

Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)

Carbon black (CAS 1333-86-4)

Copper (CAS 7440-50-8)

Iron oxide (CAS 1309-37-1)

Kaolin (CAS 1332-58-7)

Propane -1,2 -diol (CAS 57-55-6)

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Talc (CAS 14807-96-6)

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

3-Iodo-2-propynyl butyl carbamate (CAS 55406-53-6)

Copper (CAS 7440-50-8)

US. California Proposition 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Arsenic (CAS 7440-38-2)

Carbon black (CAS 1333-86-4)

Diphenyl ketone (CAS 119-61-9)

Ethylene oxide (CAS 75-21-8)

Lead (CAS 7439-92-1)

Methanol (CAS 67-56-1)

Nickel (CAS 7440-02-0)

Quartz (CAS 14808-60-7)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-November-2016

Revision date -

Version # 01

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 2*
Flammability: 1
Physical hazard: 0

Disclaimer Kelly-Moore Paint Co., Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.