



1285 ACRY-SHIELD

Alkyd Modified Acrylic Exterior Semi-Solid Stain

Product Description

A premium quality, exterior, semi-solid stain. Available in four ready mix colors. Enriches the natural beauty of resawn woods, such as redwood, cedar, cedar shakes, fir, pine, hemlock, etc., by allowing the natural grain and texture of the wood to show through. Excellent for commercial or residential application.

LIMITATION: For vertical surfaces only. Do not apply to decks.

Performance Features

- **Excellent Weather Resistance**
- **Excellent Color Retention**
- **Allows texture and grain to show**
- **Wide choice of color and opacity**
- **Low Odor & VOC**
- **Easy Application**
- **Easy Soap & Water clean-up**

Compliance - Performance - Certification

- ✓ Meets Green Seal GS-11 VOC Limits
- ✓ Meets CARB VOC Limits
- ✓ Meets SCAQMD VOC Limits
- ✓ Meets National AIM VOC Limits

Product Specifications

Resin Type:	Vinyl Acrylic, Alkyd, Oil 601 Cedar, 602 Western
Color Range:	Brown, 603 Redwood, 604 Mesa Brown
Finish:	Penetrating, semi-solid
Drying Time: (75° F. & 50% R.H.)	To Touch: 1 hour To Recoat: 4 hours
Practical coverage:	200-400 sq. ft. per gallon
Recommended Film Thickness:	Non-film forming
Weight per Gallon:	9.4 lbs.
Solids by Weight:	42%
Solids by Volume:	35%
Shelf Life:	2 years unopened
Sizes:	One & Five gallon containers
V.O.C.	<70 grams per liter
Clean Up:	Water, a final solvent wash may be desirable.

Surface Preparation

General:

All surfaces must be cured, firm, dry and cleaned free of paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. To insure maximum adhesion, the substrate must be free of all dead wood fibers. **Note:** When wood is milled, the process leaves the surfaces of the wood hard and slick. This condition is known as "Mill Glaze". If this condition exists at time of application, it will not allow stains to properly penetrate the surface of the wood. This surface of the wood should be sanded thoroughly to create surface profile. After sanding, wet the wood surfaces with water. Wetting will enhance the porosity of the surfaces to be stained. Allow the wood to dry thoroughly prior to coating application. On previously stained surfaces test for penetration and color acceptance. Do not use on previously painted surfaces unless all paint is removed.

Application: Brush or Spray

Brush: Use synthetic bristle brush.

Spray: For airless sprayers use .013 to .015 spray tip. Back brushing is recommended when spraying.

Do not apply when material, air, and/or surface temperature is below 50°F or if rain is imminent. Extremely high or low temperature or periods of high relative humidity may adversely affect dry time. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks. Avoid applying in direct sunlight.

Continued Next Page

1285 (cont.)

CAUTION: Kelly-Moore assumes no responsibility whatsoever for variations in color, or color acceptability, after application. Always apply a test sample on wood to be stained prior to application. Color and color intensity will vary depending on the degree of porosity, texture and type of wood. Use care in application because color depth increases rapidly with successive coats and where overlapping occurs. Due to the nature of the product, color uniformity cannot always be maintained from batch to batch.

Store at room temperature. Keep from freezing.

Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

Precautions

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION.

KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.