



2030 SILVER SHIELD

Aluminum Paint

Product Description

A ready-mixed bright aluminum paint for interior or exterior use. Produces a durable light and heat reflecting finish.

Performance Features

- Durable
- Excellent Light Reflectance
- Excellent Adhesion
- Excellent Coverage
- Interior/Exterior Use

Product Specifications

Resin Type:	Alkyd/Linseed Oil
Color Range:	Aluminum
Finish:	Gloss 80 on 60° gloss meter (MPI Gloss Level 6)
Drying Time: (75° F. & 50% R.H.)	To touch: 2 - 4 hours To recoat: 24 hours.
Practical Coverage:	Approx. 400-500 sq ft/gallon
Recommended Dry Film Thickness:	1.4-1.8 mils per coat
Weight per Gallon:	7.75 lbs.
Solids by Weight:	54%
Solids by Volume:	44%
Shelf Life:	2 years (unopened containers)
Sizes:	Five & one gallon
V.O.C.	<500 Grams per liter
Clean Up:	Mineral Spirits

Surface Preparation

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

General:

All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalky or loose paint, rust, loose mill scale, bond breakers and curing compounds, efflorescence, asphalt stains, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, glazed or dense surfaces. Fill holes and surfaces irregularities with a suitable patching compound to match the surface profile.

System Recommendations

Metal (Ferrous):

PRIMER: 1711 Kel-Guard White R.I. Primer

Metal (Galvanized):

PRIMER: 1725 Acry-Shield 100% Acrylic Metal Primer

Masonry:

PRIMER: 247 Acry-Shield 100% Acrylic Masonry Primer

Wood:

PRIMER: (Exterior) 220 Weather Shield Exterior Alkyd Primer
(Interior) 985 Flo-Cote Enamel Undercoat

FINISH: 2030 Silver-Shield Aluminum Paint

Application

Brush, roll, or spray. Maintain a wet edge to avoid lap marks. Do not apply when material, air, and/or surface temperature is below 40°F. Extremely high or low temperature may adversely affect dry time. Stir thoroughly before and during use.

Continued Next Page

2030 SILVER SHIELD (Cont.)

Thinning

This product has been formulated to comply with current regulations. DO NOT THIN.

Precautions

WARNING! COMBUSTIBLE LIQUID AND VAPOR.

Contains Mineral Spirits. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. **Keep away from heat and flame.** Do not smoke. Prevent build-up of vapors in enclosed areas by opening all windows and doors to achieve cross-ventilation during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave area. Always wear respiratory protection during spray application. Close container after each use. Avoid contact with eyes and skin. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. If swallowed, get medical attention immediately. For additional safety information, consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION.
KEEP OUT OF REACH OF CHILDREN.

Danger! Rags, Steel Wool or Waste soaked with linseed oil may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool, or waste in a sealed water-filled container.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.