

THIS PRODUCT MAY NOT BE AVAILABLE IN SOME AREAS DUE TO VOC REGULATIONS  
Contact your Kelly-Moore representative for more information

### Product Description

A fast drying, self-sealing, clear synthetic alkyd formulated to seal interior wood surfaces. Features quick drying and easy sanding. Do not use under urethanes.

### Performance Features

- **Fast Dry**
- **Easy Sanding**
- **Good Flow & Leveling**
- **Equalizes Surface Porosity**
- **Easy Application**

### Product Specifications

Resin Type:	Alkyd
Color Range:	Clear
Finish:	Semi-Gloss: 70 @ 60° MPI Gloss Level 5)
Drying Time: (75° F. & 50% R.H.)	To touch: 30 minutes. To recoat: 2 hours.
Coverage:	Approx. 300-400 sq ft/gallon
Recommended Dry Film Thickness:	1.5 mils per coat
Weight per Gallon:	7.1 lbs.
Solids by Weight:	37%
Solids by Volume:	30%
Shelf Life:	2 years (unopened containers)
Sizes:	Quarts
V.O.C.	<540 Grams per Liter
Clean Up:	Mineral Spirits

### Product Analysis before tinting (by weight)

<b>PIGMENT COMPOSITION</b>	<b>2%</b>
Zinc Stearate	2%
<b>VEHICLE COMPOSITION</b>	<b>98%</b>
Alkyd Resin:	34%
Solvent, Driers, Additives :	64%

### Surface Preparation

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### General:

All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalky or loose paint, rust, loose mill scale, bond breakers and curing compounds, efflorescence, asphalt stains, mildew or any other contamination or condition that would adversely affect the performance of the coating.

**New Wood:** Sand to a smooth surface and dust thoroughly. Stain, if desired, then apply a sealer coat of 2164 EZ Sand. Fill holes with a suitable putty to match wood tone color after application of sealer coat.

**Previously Varnished Wood:** Sand to remove gloss and dust thoroughly. If old varnish is checked, cracked or otherwise in poor condition, it should be removed and surface treated as 'New Wood'.

### System Recommendations

**FINISH:** Alkyd Varnish or other compatible clear finish or use 2164 EZ Sand as finish.

### Application

Brush or spray. Apply a full, even coat. Maintain a wet edge to avoid lap marks. Sand between coats and dust thoroughly. Do not apply when material, air, and/or surface temperature is below 40°F. Stir thoroughly before and during use.

### Thinning

This product has been formulated to comply with current regulations. DO NOT THIN.

*Continued Next Page*

# 2164 EZ Sand (cont.)

---

## Precautions

### Contains Petroleum Distillates and Linseed Oil.

**Flammable.** Keep away from heat, sparks and flame. Vapors can travel long distances and may ignite explosively. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation or by using explosion-proof exhaust fans both during and after application. Prevent spontaneous combustion of spray residues, rags and other waste material contaminated with this product by immediately immersing them in water for disposal.

**Vapor Harmful.** Do not breathe vapors or spray mist. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Wear a properly fitted organic vapor respirator (NIOSH/MSHA TC-23C or equivalent) until fumes are gone or leave the area. Close container after each use. Do not transfer contents to other containers for storage.

**First Aid:** In case of eye contact, flush with plenty of water for at least 15 minutes and get medical attention if irritation persists. For skin contact, wash with soap and water thoroughly. If affected by vapor inhalation, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get prompt medical attention. If swallowed, call physician immediately. Never give anything by mouth to an unconscious person.

**Notice:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

USE ONLY WITH ADEQUATE VENTILATION.  
KEEP OUT OF REACH OF CHILDREN.

## Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

**Limited Warranty:** The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.