



2687 KEL-AQUA

Interior 100% Acrylic Satin Enamel

Product Description

A professional quality, interior, 100% Acrylic satin enamel. Designed for application to properly primed interior woodwork, doors, paneling, cabinets and trim. Provides a durable, washable and decorative finish that dries quickly to minimize dust pick-up. A water thinned alternative to solvent thinned lacquers and enamels. Designed especially for spray application. Good for commercial and residential application.

Performance Features

- Durable
- Washable
- Good Block Resistance
- Fast Dry
- Excellent for Spray Application
- Easy Application
- Water Clean-Up

Compliance - Performance - Certification

- ✓ Meets Green Seal GS-11 VOC Limits
- ✓ Meets LEED EQ Credit 4.2 VOC Limits
- ✓ Meets CARB VOC Limits
- ✓ Meets National AIM VOC Limits

Product Specifications

Resin Type:	100% Acrylic
Color Range:	White & Custom Colors
Finish:	Satin @ 60° (MPI Gloss Level 4)
Drying Time: (75° F. & 50% R.H.)	To touch: 30 minutes To recoat 1 hour
Practical coverage:	Approx. 300-400 sq ft/gallon
Recommended Film Thickness:	Wet: 4.5 – 5.5 mils per coat Dry: 1.4 – 1.8 mils per coat
Weight per Gallon:	10.7 lbs.
Solids by Weight:	48%
Solids by Volume:	33%
Shelf Life:	2 years (unopened containers)
Sizes:	One & five gallon containers
V.O.C.	<100 Grams per liter
Clean Up:	Water

09 90 00 PAINTING AND COATING

Surface Preparation

General:

All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sanding glossy, dense or glazed surfaces will improve adhesion*.

**See warning for existing leaded paint under Precautions.*

New Wood:

Follow general surface preparation guidelines. Prior to application of undercoat, sand and putty nail holes and wipe woodwork clean. Sand again after application of undercoat and remove dust with clean damp rags before finish is applied. Do **not** use tack rags.

Previously Painted Surfaces: Remove any peeling or loosely adhering paint, sand to feather edges, dust clean. Gloss enamels other hard surfaces may require a bonding primer.

Continued Next Page

2687 KEL-AQUA (cont.)

System Recommendations

New Wood:

PRIMER: 2680 Kel-Aqua Interior Acrylic Enamel Undercoater

FINISH: 2687 Kel-Aqua 100% Acrylic Satin Enamel

Previously Painted Surfaces:

PRIMER: 2680 Kel-Aqua Interior Acrylic Enamel Undercoater

OR: 295 Uni-Prime All-Purpose Primer

OR: Self Prime

FINISH: 2687 Kel-Aqua 100% Acrylic Satin Enamel

Application: Brush, Roll, or Spray

Brush: Use synthetic bristle brush for small areas only.

Roller: Use 1/4" to 1/2" nap quality roller cover for small areas only.

Spray: Airless sprayer use .013 to .015 orifice tip. For conventional or HVLP sprayers please consult sprayer manual for waterborne enamels.

Do not apply when material, air, and/or surface temperature is below 50°F or above 90° F. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

Store at room temperature. Keep from freezing.

Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

Precautions

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION.

KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.