



285 KEL-BOND ULTRA

— Interior/Exterior —
Waterborne High Build
Bonding Primer-Sealer

Product Description

A waterborne, high build, flexible, bonding primer-sealer designed to reduce cracking and peeling of acrylic latex top coats as well as fill in rough surfaces to create a smoother, more uniform finish. Do not use under alkyd, epoxy, urethane, interior flat wall paints or other non-flexible finishes. Do not use on floors.

Performance Features

- High Build (up to 10 mils DFT)
- Low Odor
- Low Temp Application (min. 40° F)
- Fast Drying
- Water Clean up

Compliance - Performance - Certification

- ✓ Meets Green Seal GS-11 VOC Limits
- ✓ Meets LEED EQ 4.2 Credit VOC Limits
- ✓ Meets CARB VOC Limits
- ✓ Meets SCAQMD VOC Limits
- ✓ Meets National AIM VOC Limits

Product Specifications

Resin Type:	Acrylic
Color Range:	Clear with Blue tint
Drying Time: (75° F. & 50% R.H.)	To Touch: 30 minutes To Recoat: 1 hour <i>Heavy films will take longer to dry.</i>
Practical coverage:	50 – 200 sq. ft. per gallon
Recommended Film Thickness:	Wet: 8 – 32 mils Dry: 2.5 – 10 mils
Weight per Gallon:	9 lbs.
Solids by Weight:	32%
Solids by Volume:	28%
Shelf Life:	2 years unopened
Sizes:	One & Five Gallons
V.O.C.	< 100 grams per liter
Clean Up:	Soap & Water

Surface Preparation

General:

All surfaces must be cured, firm, dry and cleaned free of loose paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces*.

*See warning for existing leaded paint under Precautions.

New Surfaces: Follow general surface preparation guidelines. All loose wood fibers should be removed. Concrete and stucco surfaces should be cured for 30 days before priming or painting.

Previously Painted Surfaces: This product is not designed to eliminate required surface preparation. All peeling, flaking or loose existing paint must be removed to a firm, clean surface.

Continued Next Page

285 (cont.)

System Recommendations

PRIMER: 285 Kel-Bond Ultra

FINISH:

Interior: Kelly-Moore Acrylic Latex Enamel (Non-Flat)

Exterior: Kelly-Moore 100% Acrylic Paint or Elastomeric Coating

Application: Brush, Roll, or Spray

Brush: Use synthetic bristle brush

Roller: Use 1/2 to 1 inch nap roller cover.

Spray: Airless sprayer recommended. Use .015 to .019 spray tip. Back rolling or back brushing will help work the primer into cracks and fissures.

Do not apply when material, air, and/or surface temperature is below 40°F or above 90° F. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

Store at room temperature. Keep from freezing.

Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

Precautions

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION.

KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.