

Product Description

A professional quality, interior, flat latex maintenance finish. Designed to dry fog within 20 feet for easy application and clean-up. Good for tall, hard to reach ceilings, walls, framing and their various substrates. Good for commercial and industrial application.

Performance Features

- Dries within 20 feet under normal conditions
- Multiple Substrate Usage
- Good Adhesion
- Low Odor & VOC
- Water Clean-up
- Non-Bridging

Compliance - Performance - Certification

- ✓ MPI Approved Products List #118
- ✓ Meets Green Seal GS-11 VOC Limits
- ✓ Meets LEED EQ Credit 4.2 VOC Limits
- ✓ Meets CARB VOC Limits
- ✓ Meets SCAQMD VOC Limits
- ✓ Meets National AIM VOC Limits

Product Specifications

Resin Type:	Styrene Butadiene
Color Range:	White, Black, MTO colors
Finish:	Flat <3 @ 60° MPI Gloss Level 1
Drying Time: (75° F. & 50% R.H.)	To Touch: 1 hour To Recoat: 4 hours
Practical coverage:	Approx. 150-250 sq. ft./gallon
Recommended Film Thickness:	Wet: 5.0 - 7.0 mils per coat Dry: 2.0 - 3.0 mils per coat
Weight per Gallon:	12.8 lbs.
Solids by Weight:	62%
Solids by Volume:	41%
Shelf Life:	2 years unopened
Sizes:	Five gallon containers
V.O.C.	<10 grams per liter
Clean Up:	Water

Surface Preparation

General:

All surfaces must be cured, firm, dry and cleaned free of loose paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces*.

*See warning for existing leaded paint under Precautions.

System Recommendations

Wallboard and Plaster:

PRIMER: 971 Acry-Plex PVA Primer/Sealer
OR: 95-102 Pre-Cote Wallboard Primer
OR: Self-priming

Wood and Hardboard:

PRIMER: 295 Kel-Bond Universal Primer
OR: Self-priming on bare wood and hardboard

Metal (ferrous, aluminum):

PRIMER: 5725 DTM Acrylic Primer/Finish

Galvanized Metal: Self-priming on properly prepared galvanized

Masonry:

PRIMER: 247 Acry-Shield 100% Acrylic Masonry Primer
OR: Self-priming on bare masonry

FINISH: 480 Dry Fog II Flat Latex Maintenance Finish

Continued Next Page

480 Dry Fog II (cont.)

Application: Brush, Roll, or Spray

Brush: Not recommended except for touch-up

Roller: Not recommended except for touch-up

Spray: Airless sprayer recommended. Use a .017 - .025 spray tip.

Do not apply directly over previously painted surfaces; always apply appropriate Kelly-Moore Primer

Do not apply when material, air, and/or surface temperature is below 50°F or above 90° F. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

Store at room temperature. Keep from freezing.

Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

Precautions

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION.

KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.