

SAFETY DATA SHEET

KM-110 PART A BASE

Page 1 – 9/9/2015

1. Product and Company Information

Product Code: KM-110 BASE
Product Name: KM-110 PART A BASE
Company Name: Kelly Moore Paints
987 Commercial Street
San Carlos, CA 94070
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
Emergency Contact: CHEMTREC: (800) 424-9300

Phone Number:
(888) 677-2468

2. Hazards Identification

Target Organ Systemic Toxicity (repeated exposure), Category 2
Flammable Liquids, Category 3
Acute Toxicity: Skin, Category 4
Skin Corrosion/Irritation, Category 2
Eye Irritation, Category 2
Acute Toxicity, Inhalation, Category 4
Skin Corrosion/Irritation, Category 3
Toxic To Reproduction, Category 1B
Aquatic Toxicity (Acute), Category 3



GHS Signal Word:

Danger

GHS Hazard Phrases:

H373 - May cause damage to organs through prolonged or repeated exposure.
H226 - Flammable liquid and vapor.
H312 - Harmful in contact with skin.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H402 - Harmful to aquatic life.

GHS Response Phrases:

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P241 - Use explosion-proof electrical/ventilating/lighting/equipment.
P243 - Take precautionary measures against static discharge.
P271 - Use only outdoors or in a well-ventilated area.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

GHS Precaution Phrases:

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P332+313 - If skin irritation occurs, get medical advice/attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313 - If eye irritation persists, get medical advice/attention.
P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.
P403+235 - Store in cool/well-ventilated place. Store locked up.
P501 - Contact a licensed professional waste disposal service to dispose of this material.

GHS Storage and Disposal Phrases:

Potential Health Effects (Acute and Chronic):

Inhalation:

Chronic inhalation may cause effects similar to those of acute inhalation. Material is irritating to mucous membranes and upper respiratory tract. Harmful if inhaled. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Vapors may cause dizziness or suffocation.

KM-110 PART A BASE/PAGE 2

Skin Contact:	May be harmful if absorbed through the skin. Prolonged and/or repeated contact may cause irritation and/or dermatitis.
Eye Contact:	Causes eye irritation. Causes redness and pain.
Ingestion:	May be harmful if swallowed. May be harmful if inhaled. May cause irritation of the digestive tract. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
14808-60-7	Silicon Dioxide	25.0 -35.0 %
1330-20-7	Xylene (mixed isomers)	20.0 -30.0 %
Proprietary	Polyamide Based Resin	10.0 -20.0 %
14807-96-6	Talc	10.0 -20.0 %
13463-67-7	Titanium Dioxide	5.0 -10.0 %
108-65-6	Propylene Glycol Methyl Ether Acetate	1.0 -10.0 %
100-41-4	Ethylbenzene	1.0 -6.0 %
84852-15-3	Phenol, 4-nonyl-, branched	1.0 -2.0 %

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation:	If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.
In Case of Skin Contact:	Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.
In Case of Eye Contact:	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.
In Case of Ingestion:	Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Get medical aid.
Signs and Symptoms Of Exposure:	Central nervous system depression. Dermatitis. Abdominal pain, Nausea. Vomiting, Anorexia. Shortness of breath.
Note to Physician:	Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media:	Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.
Fire Fighting Instructions:	Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable Liquid. Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.
Flammable Properties and Hazards:	Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled:

Personal precautions.
Use personal protective equipment.
Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.

KM-110 PART A BASE/PAGE 3

7. Handling and Storage

Precautions To Be Taken in Handling:

Avoid contact with skin and eyes. Normal measures for preventive fire protection. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

Precautions To Be Taken In Storing:

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Suitable: Keep away from heat, sparks, and open flame.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA
14808-60-7	Silicon Dioxide	PEL: 8825 ppm/(%SiO ₂ +5)	TLV: 0.05 mg/m ³ (R)
1330-20-7	Xylene (mixed isomers)	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm
Proprietary	Polyamide Based Resin	N/A	N/A
14807-96-6	Talc	PEL: 706 ppm/20 mppcf	TLV: 2 mg/m ³ (non-asbestos)
13463-67-7	Titanium Dioxide	PEL: 15 (dust) mg/m ³	TLV: 10 mg/m ³
108-65-6	Propylene Glycol Methyl Ether Acetate	N/A	N/A
100-41-4	Ethylbenzene	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm
84852-15-3	Phenol, 4-nonyl-, branched	N/A	N/A

Respiratory Equipment (Specify Type):

For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

Eye Protection:

Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves:

Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.)

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Work/Hygienic/Maintenance Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Physical States:	<input type="checkbox"/> Gas	<input checked="" type="checkbox"/> Liquid	<input type="checkbox"/> Solid
Flash Point:	80 ° F		
Boiling Point:	284° F		
Explosive Limits:	LEL: 1.0	UEL: 7.1	
Weight Per Gallon:	12.45 +/- .3		
Vapor Pressure (mm Hg):	7.0 @ 68 ° F		
Vapor Density:	Heavier than Air		
Evaporation Rate:	Slower than Ether		
Percent Volatile:	49 (VOL)		

10. Stability and Reactivity

Stability:	Unstable [<input type="checkbox"/>]	Stable [<input checked="" type="checkbox"/>]
Conditions To Avoid – Instability:	Heat, flames and sparks. Incompatible materials, ignition sources.	
Incompatibility - Materials To Avoid:	Strong acids, Strong oxidizing agents.	
Hazardous Decomposition Or Byproducts:	Nature of decomposition products unknown.	
Possibility of Hazardous Reactions:	Will occur [<input type="checkbox"/>]	Will not occur [<input checked="" type="checkbox"/>]

KM-110 PART A BASE/PAGE 4

11. Toxicological Information

Toxicological Information:

Respiratory or skin sensitization: Germ cell mutagenicity. Reproductive toxicity - no data available. Specific target organ toxicity -single exposure (Globally Harmonized System) Specific target organ toxicity -repeated exposure (Globally Harmonized System)
Inhalation: May cause damage to organs through prolonged or repeated exposure. Aspiration hazard.
Epidemiology: No information available.
Teratogenicity: No information available.

Irritation or Corrosion:

No data available.

Sensitization:

No data available.

Carcinogenicity/Other

Information:

These products contain more than 0.1% crystalline silica (CAS #14808-60-7) which has been classified by IARC a Class 1 carcinogen. Normal application procedures pose no hazard since the silica is set and encapsulated, but grinding or sanding dried films may yield respirable silica dusts. Control exposures to less than 0.1 mg per cubic meter of air using approved dust filter respirators. Skin contact: Prolonged or repeated contact with product may cause slight skin irritation. Impervious gloves should be worn if prolonged skin contact is likely.

ACGIH Carcinogens

Quartz (CAS 14808-60-7)

A2 Suspected human carcinogen

IARC Monographs, Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7)

1 Carcinogenic to humans

US NTP Report on Carcinogens: Known carcinogen

Quartz (CAS 14808-60-7)

Known to be human carcinogen

OSHA PEL: Exposure to airborne crystalline silica shall not exceed an 8 hour time weighted average limit as stated in 29CFR 1910.1000, Table-Z-1-A Air contaminants, specifically: Silica, Crystalline Quartz (Respirable) 0.1 MG/M3. ACGIH TLV-TWA: 01 MG/M3. NIOSH Maximum permissible conc. 0.05 MG/M3, 10 hour workday, 40 hour week. This product contains the following substances known to the State of California to cause cancer, birth defects, or other reproductive hazards: Benzene, Toluene, Crystalline Silica.

12. Ecological Information

General Ecological Information:

No data available.

Persistence and Degradability:

No data available.

Bioaccumulative Potential:

No data available.

Mobility in Soil:

No data available.

13. Disposal Considerations

Waste Disposal Method:

Dispose of as unused product. This material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT):

Consumer commodity – ORM-D – Used for 1 gallon containers when shipped in the United States of America.

DOT Proper Shipping Name:

UN1263, Paint Related Material, 3, PG III – 5 Gallon pails



Marine Transport IMDG Shipping:

UN1263, Paint Related Material, 3, PG III



AIR TRANSPORT (ICAO/IATA):

UN1263, Paint Related Material, 3, PG III

IATA Shipping Name:



KM-110 PART A BASE/PAGE 5

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
14808-60-7	Silicon Dioxide	No	No	No
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes
Proprietary	Polyamide Based Resin	No	No	No
14807-96-6	Talc	No	No	No
13463-67-7	Titanium Dioxide	No	No	No
108-65-6	Propylene Glycol Methyl Ether Acetate	No	No	No
100-41-4	Ethylbenzene	No	Yes 1000 LB	Yes
84852-15-3	Phenol, 4-nonyl-, branched	No	No	No

V.O.C. MIXED: 3.30 LBS/GL (395 GMS/L)

16. Other Information

Revision Date: 9/9/2015

Additional Information About This Product:

Hazardous Material Information System III (U.S.A)

Health: 2*
Flammability: 3
Reactivity: 0
Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Kelly Moore Paint Co. and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.