

SAFETY DATA SHEET

KM-145 PART B HARDENER

Page 1 – 10/22/2015

1. Product and Company Identification

Product Code: KM-145 HARD
Product Name: KM-145 PART B HARDENER
Company Name: Kelly Moore Paints
987 Commercial Street
San Carlos, CA 94070
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
Emergency Contact: CHEMTREC: (800) 424-9300

Phone Number:
(888) 677-2468

2. Hazards Identification

Skin Sensitization, Category 1
Flammable Liquids, Category 3
Acute Toxicity: Skin, Category 4
Skin Corrosion/Irritation, Category 2
Acute Toxicity: Inhalation, Category 4
Target Organ Systemic Toxicity (repeated exposure), Category 2
Target Organ Systemic Toxicity (single exposure), Category 3



GHS Signal Word:
GHS Hazard Phrases:

Danger

H317 – May cause an allergic skin reaction.
H226 – Flammable liquid and vapor.
H312 – Harmful in contact with skin.
H315 – Causes skin irritation.
H332 – Harmful if inhaled.
H373 – May cause damage to organs through prolonged or repeated exposure.
H335 – May cause respiratory irritation.

GHS Precaution Phrases:

P261 – Avoid breathing dust/fume/gas/mist/vapors/spray.
P272 – Contaminated work clothing should not be allowed out of the workplace.
P280 – Wear protective gloves/protective clothing/eye protection/face protection.
P233 – Keep container tightly closed.
P210 – Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P241 – Use explosion-proof electrical/ventilating/lighting/equipment.
P242 – Use only non-sparking tools.
P264 – Wash hands thoroughly after handling.
P271 – Use only outdoors or in a well-ventilated area.

GHS Response Phrases:

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P332+313 - If skin irritation occurs, get medical advice/attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313 - If eye irritation persists, get medical advice/attention.
P301+330+331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.

GHS Storage and Disposal Phrases:

P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.
P403+235 – Store in cool/well-ventilated place. Store locked up.

Potential Health Effects (Acute and Chronic):

P501-Contact a licensed professional waste disposal service to dispose of this material.
Repeated or prolonged exposure may cause CNS stimulation.
Chronic inhalation can cause pneumoconiosis. Chronic inhalation may cause effects similar to those of acute inhalation.

Inhalation:

Material is irritating to mucous membranes and upper respiratory tract. Harmful if inhaled. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Vapors may cause dizziness or suffocation.

Skin Contact:

May be harmful if absorbed through the skin. Prolonged and/or repeated contact may cause irritation and/or dermatitis.

Eye Contact:

Causes eye irritation. Causes redness and pain.

KM-145 PART B HARDENER/PAGE 2

Ingestion:

May be harmful if swallowed. May be harmful if inhaled. May cause irritation of the digestive tract. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

3. Composition on Ingredients

| CAS # | Hazardous Components (Chemical Name) | Concentration |
|------------|--------------------------------------|---------------|
| 14807-95-5 | Talc | 35.0 – 45.0% |
| 13463-67-7 | Titanium dioxide | 20.0 – 30.0% |
| 64742-95-6 | Aromatic Solvent | 18.0 – 25.0% |
| 68410-23-1 | Polyamide based resin | 14.0 – 20.0% |
| 1330-20-7 | Xylene (mixed isomers) | 4.0 – 8.0% |
| 107-98-2 | 2-Propanol, 1-Methoxy- | 1.0 – 10.0% |
| 100-41-4 | Ethylbenzene | 0.0 – 2.0% |

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation:

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.

In Case of Skin Contact:

Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.

In Case of Eye Contact:

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion:

Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Get medical aid.

Note to Physician:

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media:

Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Fire Fighting Instructions:

Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Flammable Properties and Hazards:

Specific Hazard(s): Flammable Liquid. Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled:

Personal precautions. Use personal protective equipment. Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.

7. Handling and Storage

Precautions To Be Taken in Handling:

Avoid contact with skin and eyes. Normal measures for preventive fire protection. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

Precautions To Be Taken in Storing:

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Suitable: Keep away from heat, sparks, and open flame.

KM-145 PART B HARDENER/PAGE 3

8. Exposure Controls/Personal Protection

| CAS # | Partial Chemical Name | OSHA TWA | ACGIH TWA |
|------------|------------------------|-----------------------|-------------------------------|
| 14807-96-6 | Talc | PEL: 706 ppm/20 mppcf | TLV: 2mg/m3 (non-asbestos) |
| 13463-67-7 | Titanium dioxide | PEL: 15 (dust) mg/m3 | TLV: 10 mg/m3 |
| 64742-95-6 | Aromatic Solvent | PEL: 100 ppm | TLV: 100 ppm STEL: 150 ppm |
| 68410-23-1 | Polyamide based resin | N/E | N/E |
| 107-98-2 | 2-Propanol, 1-Methoxy- | PEL: 100 ppm | TLV: 100 ppm STEL: 150 ppm |
| 1330-20-7 | Xylene (mixed isomers) | PEL: 100 ppm | TLV: 100 ppm STEL: 150 ppm |
| 100-41-4 | Ethylbenzene | PEL: 100 ppm | TLV: 100 ppm STEL: 125 ppm |

Respiratory Equipment (Specify Type):

For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

Eye Protection:

Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves:

Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

(Ventilation etc.):

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Work/Hygienic/Maintenance Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse.

9. Chemical and Physical Properties

| | | | |
|--------------------------------|------------------------------|--|--------------------------------|
| Physical States: | <input type="checkbox"/> Gas | <input checked="" type="checkbox"/> Liquid | <input type="checkbox"/> Solid |
| Appearance and Odor: | Solid Color, Aromatic odor | | |
| Boiling Point: | 280 ° F | | |
| Flash Pt: | 80 ° F | | |
| Explosive Limits: | LEL: 1.2 | UEL: 13.74 | |
| Weight Per Gallon: | 13.70 +/- .3 | | |
| Vapor Pressure (mm Hg): | 11.8 @ 77° F | | |
| Vapor Density: | Heavier than air | | |
| Evaporation Rate: | Slower than Ether | | |
| Percent Volatile: | 50 (vol.) | | |

10. Stability and Reactivity

| | | |
|---|--|--|
| Stability: | Unstable <input type="checkbox"/> | Stable <input checked="" type="checkbox"/> |
| Conditions To Avoid – Instability: | Ignition sources, Excess heat, Heat, flames and sparks | |
| Incompatibility – Materials To Avoid: | Strong oxidizing agents. | |
| Hazardous Decomposition Or Byproducts: | Nature of decomposition products unknown | |
| Possibility of Hazardous Reactions: | Will occur <input type="checkbox"/> | Will not occur <input checked="" type="checkbox"/> |
| Conditions To Avoid – Hazardous Reactions: | No data available. | |

11. Toxicological Information

| | |
|-----------------------------------|---------------------------|
| Toxicological Information: | No information available. |
| Irritation or Corrosion: | No data available. |

KM-145 PART B HARDENER/PAGE 4

Chronic Toxicological Effects:

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

This product contains substances known to the State of California to cause Cancer, Birth Defects, or other reproductive hazards: Benzene, Toluene.

12. Ecological Information

General Ecological Information:

No data available

Persistence and Degradability:

No data available.

Bioaccumulative Potential:

No data available.

Mobility in Soil:

No data available

13. Disposal Considerations

Waste Disposal Method:

Dispose of as unused product. This material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name:

UN1263, Paint Related Material, 3, PG II



IMDG Shipping Name:

UN1263, Paint Related Material, 3, PG II



AIR TRANSPORT (ICAO/IATA)

IATA Shipping Name:

UN1263, Paint Related Material, 3, PG II



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

| CAS # | Hazardous Components (Chemical Name) | S. 302 (EHS) | S. 304 RQ | S. 313 (TRI) |
|------------|--------------------------------------|--------------|-------------|--------------|
| 14807-96-6 | Talc | No | No | No |
| 13463-67-7 | Titanium dioxide | No | No | No |
| 64742-95-6 | Aromatic Solvent | No | No | No |
| 68410-23-1 | Polyamide based resin | No | No | No |
| 107-98-2 | 2-Propanol, 1-Methoxy- | No | No | No |
| 1330-20-7 | Xylene (mixed isomers) | No | Yes 100 LB | Yes |
| 100-41-4 | Ethylbenzene | No | Yes 1000 LB | Yes |

V.O.C (mixed) 2.83 LBS/GL (339 GMS/L)

KM-145 PART B HARDENER/PAGE 5

16. Other Information

Revision Date: 10/22/2015

Additional Information About This Product:

Hazardous Material Information System III (U.S.A.)

Health: 2*

Flammability: 3

Reactivity: 0

Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks and 4 representing significant hazards or risks. Although HMIS® ratings are to be used with a fully implemented HMIS® program, HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J.J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Kelly Moore Paint Co. and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.