

**MATERIAL SAFETY DATA SHEET**  
**For Coatings Resins & Related Materials**

===== **Section I** =====

Manufactured For:	Kelly-Moore Paints	Prep Date: 07/28/06
Address:	987 Commercial Street San Carlos, CA 94070	Emergencies Involving Spills, Leaks, Fires, Exposure, Or Accident Contact Chemtrec: 1-800-424-9300
Product Class:	Epoxy Curing Hardener	Information Phone: 1-888-677-2468
Trade Name:	<b>KM-1702-002 PART B HARDENER</b>	
H.M.I.S. Codes:	H F R P 3 1 0 -	

===== **Section II - HAZARDOUS INGREDIENTS** =====

Ingredient	C.A.S.#	Weight Percent	Occup. Exposure Limits		Vapor Pressure mm Hg & Temp.F
			OSHA PEL	ACGIH TLV	
Cycloaliphatic Amines Mixture		60-70	Not Established		Not Established
Benzyl Alcohol	101-56-6	30-40	Not Established		<1 68

\*Indicates toxic chemical(s) subject to reporting requirements of Section 313 of Title III and of 40 CFR 372.

===== **Section III - PHYSICAL DATA** =====

Boiling Range (Deg. F): 280	Vapor Density: Heavier than air
Evaporation Rate: N/A	
Percent Volatile By Volume: 0	Weight Per Gallon (lbs.): 8.6 ± .2

===== **Section IV - FIRE & EXPLOSION HAZARD DATA** =====

Flash Point (Deg. F): >200°	Lower Explosive Limit: N/A
Extinguishing Media: Foam, CO2, dry chemical, water spray	

OSHA Flammability Classification: Combustible Liquid, Class III B

Special Firefighting Procedures: Wear a NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing. Use water to keep fire exposed containers cool.

Unusual Fire & Explosion Hazards: Vapors are heavier than air and may travel along the ground or be moved by ventilation to ignition sources at locations distant from material handling point. Pressure may build up in containers and create an explosion hazard.

**KM-1702-002 PART B HARDENER**

**=====  
Section V - HEALTH HAZARD DATA  
=====  
THIS PRODUCT IS CORROSIVE**

**Effects Of Overexposure:**

**Eyes:** Irritation, burning, tearing, redness, swelling, possible chemical burns.

**Skin:** Severe irritation, possible skin sensitizer. Can cause chemical burns, redness, and swelling.

**Ingestion:** Abdominal pain, nausea, vomiting, diarrhea, throat and mouth burns.

**Inhalation:** Headache, nausea, respiratory tract irritant.

**Emergency & First Aid Procedures:**

**Eyes:** Flush with water for 15 minutes.

**Skin:** Remove contaminated clothing, wash skin with soap and water.

**Ingestion:** Do not induce vomiting. Get medical treatment immediately.

**Inhalation:** Move to fresh air, aid breathing if necessary.

In all cases, consult a physician for best treatment.

Chemical listed as carcinogen or potential carcinogen:

NTP: No      IARC: No      OSHA: No

**=====  
Section VI - REACTIVITY DATA  
=====**

Stability: Product Stable

Conditions to Avoid: All sources of ignition

Incompatibility (Materials to Avoid): Oxidizing agents, strong acids & bases

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, nitrogen oxides and organic compounds.

Hazardous Polymerization: Will Not Occur

**=====  
Section VII - SPILL OR LEAK PROCEDURES  
=====**

Steps To Be Taken In Case Material Is Released Or Spilled: Dike spill area. Absorb spill with inert absorbent material. Place in sealed metal containers for proper disposal.

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations.

**=====  
Section VIII - SPECIAL PROTECTION INFORMATION  
=====**

Respiratory Protection: Use a NIOSH/MSHA jointly approved respirator

Ventilation: Use mechanical ventilation

Protective Gloves: Neoprene or rubber

Eye Protection: Chemical splash goggles

Other Protective Equipment: Protective clothing, barrier cream, eye bath, safety shower

**=====  
Section IX - SPECIAL PRECAUTIONS  
=====**

Precautions To Be Taken In Handling & Storing; Store in dry area. Keep away from open flames and high temperatures.

Other Precautions: Minimize contact. Avoid breathing vapors. Practice good industrial hygiene and safe working practices.