



# 1111 KEL-TEX

## Exterior Acrylic Medium Texture Coating

### Product Description

A premium quality multi-mil acrylic medium texture coating formulated to color coat and texture in one operation on new or existing masonry surfaces. Properly applied, Kel-TEX provides long term weather resistance and color retention and is a "breathing film" allowing water vapor to escape from the surface without loss of adhesion. Kel-TEX helps conceal minor surface defects and provides an attractive appearance that is both decorative and protective. May also be applied to properly prepared and primed ferrous metal, galvanized metal or aluminum.

### Performance Features

- Textured Finish
- High Build
- Self-Priming on Cured Concrete
- Performance Equal to TT-C-555
- Water Clean-up

### Compliance - Performance - Certification

- ✓ MPI Approved Product Category #42
- ✓ Meets MPI GPS-1
- ✓ Meets Green Seal GS-11 VOC Limits
- ✓ Meets CARB VOC Limits
- ✓ Meets National AIM VOC Limits

### Product Specifications

Resin Type:	100% Acrylic
Color Range:	White & custom tints
Finish:	Flat, medium texture
Drying Time:	To Touch: 1 hour (75° F. & 50% R.H.) To Recoat: 24 hours
Practical coverage:	50-100 sq. ft. per gallon
Recommended Film Thickness:	Wet: 15-30 mils Dry: 10-20 mils
Weight per Gallon:	8.55 lbs.
Solids by Weight:	60%
Solids by Volume:	59%
Shelf Life:	2 years unopened
Sizes:	Five gallon containers
V.O.C.	<50 grams per liter
Clean Up:	Water

### Surface Preparation

#### General:

All surfaces must be cured, firm, dry and cleaned free of loose paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces\*.

*\*See warning for existing leaded paint under Precautions.*

**New Surfaces:** Follow general surface preparation guidelines. New concrete or stucco should be allowed to cure for 30 days prior to painting. Moisture content should be less than 12 % as measured with a moisture meter and the pH should be between 7 and 11. Remove all laitance and efflorescence before priming with the appropriate primer.

**Previously Painted Surfaces:** Follow general surface preparation guidelines. Remove loose or failing paint and spot prime bare areas or entire surface with the appropriate primer. Hard, glossy surfaces may require sanding and/or a bonding primer.

*Continued Next Page*

# 1111 (cont.)

---

## System Recommendations

### Concrete, Stucco & Masonry

PRIMER: 247 Acry-Shield 100% Acrylic Masonry Primer  
OR: Self Priming on Cured Concrete

### Concrete Block:

PRIMER: 521 Prime & Fill Acrylic Block Filler

### Ferrous Metal, Galvanized Metal or Aluminum:

PRIMER: 1725 Kel-Guard 100% Acrylic Metal Primer

FINISH: 1111 Kel-Tex Acrylic Medium Textured Coating

## Application: For Spray Application

Brush: For minor touch-up. Use synthetic bristle brush

Roller: Not recommended

Spray: Use a texture sprayer such as Graco's RTX 1500 or equivalent. Consult sprayer manual for proper tip assembly.

Do not apply when material, air, and/or surface temperature is below 50°F or above 90° F. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

Store at room temperature. Keep from freezing.

## Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

## Precautions

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information consult the Material Safety Data Sheet for this product.

**USE ONLY WITH ADEQUATE VENTILATION.**

**KEEP OUT OF REACH OF CHILDREN.**

## Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

**Limited Warranty:** The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.