



# 122 KEL-PRO

## Vinyl Block Filler

### Product Description

A professional quality, interior/exterior, heavy-bodied acrylic block filler. Designed to fill and seal porous interior or exterior concrete block surfaces. Good for commercial application.

### Performance Features

- Uniforms Substrate
- Low Odor and VOC
- Easy Application

### Product Specifications

Resin Type	Vinyl Acrylic
Color Range	Off White
Drying Time (75° F. & 50% R.H.)	To touch: 1-4 hours To recoat: 48 hours.
Practical Coverage	approx. 50-75 sq. ft./gallon
Recommended Dry Film Thickness	11 mils per coat
Weight Per Gallon	13.8 lbs.
Solids By Weight	71%
Solids By Volume	53%
Shelf Life	2 years (unopened containers)
Sizes	Five gallon containers
V.O.C.	<55 Grams per liter
Clean Up	Water

### Product Analysis (by weight)

PIGMENT COMPOSITION		60%
Calcium Carbonate:		54%
Silicates:		6%
VEHICLE COMPOSITION		40%
Vinyl Acrylic Resin:		11%
Water, Surfactants, Defoamers:		29%

### Surface Preparation

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### General:

All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalky or loose paint, rust, loose mill scale, bond breakers and curing compounds, efflorescence, asphalt stains, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, glazed or dense surfaces. Fill holes and surfaces irregularities with a suitable patching compound to match the surface profile.

### New Masonry, Concrete & Stucco:

Follow general surface preparation guidelines. Remove all burrs, nibs, and mortar splatters. Point up mortar joints, fill large voids and other surface irregularities with suitable patching compounds to match surface profile. New Concrete or Stucco should be allowed to cure for 30 days. Prime with the specified primer.

### Previously Painted (Unfilled) Masonry:

Prime entire surface with Kel-Pro 122 Vinyl Block Filler.

### System Recommendations

#### Masonry:

PRIMER: 122 Kel-Pro Vinyl Block Filler

FINISH: Appropriate Kelly-Moore finish.

*Continued Next Page*

# 122 KEL-PRO (cont.)

## Application

Brush, Roll or Spray. Do not apply when material, air, and/or surface temperature is below 50°F. Apply in a manner to achieve a uniform film free of voids and pinholes. If sprayed, better filling of surface pits, voids and cracks is achieved by back rolling.

## Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

## Precautions

**Contains Crystalline Silica.** Always wear a particle mask to limit exposure to paint dust when spraying this product and when sanding or grinding dry painted surfaces. **WARNING:** Crystalline Silica has been listed by the State of California as a carcinogen. Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. Protect from freezing. For additional safety information, consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION  
KEEP OUT OF REACH OF CHILDREN.

## Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

**Mildew:** This paint has been formulated to be mildew resistant, however, it will not mildew-proof the surface nor completely prevent or destroy mildew. Therefore, Kelly-Moore Paint Company Inc. assumes no responsibility for mildew development.

**Limited Warranty:** The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.