



2096 KEL-THANE II

Waterborne Interior Clear Gloss Finish

Product Description

A premium quality, interior, acrylic/urethane, clear gloss finish. Designed exclusively for interior wood surfaces such as doors, trim, paneling, furniture, cabinets, and floors. May also be used over painted wood surfaces where extra protection against abrasion, soil and stain is required. Provides a low odor, fast drying and crystal clear finish. Also available in semi-gloss (2094) and satin (2097) finishes. Excellent for commercial and residential application.

Performance Features

- **Excellent Durability**
- **Excellent Abrasion Resistance**
- **Excellent Clarity**
- **Non Yellowing**
- **Fast Drying**
- **Low Odor**
- **USDA Acceptable**

Compliance - Performance - Certification

- ✓ Meets LEED EQ Credit 4.2 VOC Limits
- ✓ Meets CARB VOC Limits
- ✓ Meets SCAQMD VOC Limits
- ✓ Meets National AIM VOC Limits

Product Specifications

Resin Type:	Acrylic/Urethane
Color Range:	Clear
Finish:	Gloss 80+ @ 60° MPI Gloss Level 6
Drying Time: (75° F. & 50% R.H.)	To Touch: 10-20 minutes To Recoat: 30-45 minutes
Practical coverage:	Approx. 450-550 sq. ft./gal.
Recommended Film Thickness:	Wet: 3.3 mils per coat Dry: 1.0 mil per coat
Weight per Gallon:	8.5 lbs.
Solids by Weight:	30%
Solids by Volume:	28%
Shelf Life:	2 years unopened
Sizes:	Gallons and Quarts
V.O.C.	<200 grams per liter
Clean Up:	Water

Surface Preparation

General:

All surfaces must be cured, firm, dry and cleaned free of loose paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces*.

*See warning for existing leaded paint under Precautions.

New Surfaces: Follow general surface preparation guidelines. If product is to be used in conjunction with stain, waterborne stains are recommended. Check for compatibility with stains or other existing sealers or finishes. Do not use over stains that contain waxes and/or stearates or over uncured oil base stains. Do not use over sanding sealers.

Application: A minimum of three coats is recommended on new or unfinished wood. Sand between coats with fine sandpaper. Remove dust with clean damp cloth. Do not use tack rags.

Do not apply when material, air, and/or surface temperature is below 50°F. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

Brush with nylon or synthetic bristle brush. For floors use a lambs wool pad. Spray is recommended for professional applicators only. Do not roll. Do not apply when material, air, and/or surface temperature is below 50°F or above 90° F. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

Floors finished with Kel-Thane II can be walked on the next day but wait 2 or 3 days before carefully replacing heavy furniture.

Continued Next Page

2096 (cont.)

Store at room temperature. Keep from freezing.

Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

Precautions

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION.

KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of **MERCHANTABILITY OR FITNESS** for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.