



# 481 DRY FOG II

## Satin Latex Maintenance Finish

### Product Description

A professional quality, interior, satin latex maintenance finish. Designed to dry fog within 20 feet for easy application and clean-up. Good for tall, hard to reach ceilings, walls, framing and their various substrates. Good for commercial and industrial application.

Conforms to Green Seal Paints GS-11 Criteria

### Performance Features

- Dries within 20 feet under normal conditions
- Multiple Substrate Usage
- Good Adhesion
- Low Odor & VOC
- Water Clean-up

### Product Specifications

Resin Type:	Styrene Butadiene
Color Range:	White and light tints
Finish:	Satin 20-25 @ 60° (MPI Gloss Level 4)
Drying Time: (75° F. & 50% R.H.)	To touch: 1 hour To recoat 4 hours.
Practical Coverage:	Approx. 200-250 sq ft/gallon
Recommended Dry Film Thickness:	2.0-3.0 mils per coat
Weight Per Gallon:	9.9 lbs.
Solids By Weight:	41%
Solids By Volume:	30%
Shelf Life:	2 years (unopened containers)
Sizes:	Five gallon containers
V.O.C.	<10 Grams per liter
Clean Up:	Water

### Product Analysis (by weight)

<b>PIGMENT COMPOSITION</b>	<b>20%</b>
Titanium Dioxide:	15%
Calcium Carbonate:	5%

<b>VEHICLE COMPOSITION</b>	<b>80%</b>
Styrene Butadiene Resin:	21%
Water, Surfactants, Defoamers:	59%

### Surface Preparation

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### General:

All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces.

### Previously Painted Surfaces:

Spot prime bare or patched areas or prime entire surface, as required. Prime lightly-chalked painted surfaces with a suitable Kelly-Moore Surface Conditioner. Loose paint and medium to heavy chalk must be removed.

### System Recommendations

#### Wallboard and Plaster:

PRIMER: 971 Acry-Plex PVA Primer/Sealer  
OR: 95-102 Pre-Cote Wallboard Primer  
OR: Self-priming

#### Wood and Hardboard:

PRIMER: 295 Uni-Prime All Purpose Primer

#### Metal (ferrous, aluminum and galvanized):

PRIMER: 1725 Acry-Shield 100% Acrylic  
Metal Primer

#### Masonry:

PRIMER: 247 Acry-Shield 100% Acrylic Masonry  
Primer

FINISH: 481 Dry Fog II

*Continued Next Page*

# 481 DRY FOG II (cont.)

---

## Application

Spray. Do not apply when material, air, and/or surface temperature is below 50°F or if rain is imminent. Extremely high or low temperature or periods of high relative humidity may adversely affect dry time. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

## Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

## Precautions

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. Protect from freezing. For additional safety information, consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION  
KEEP OUT OF REACH OF CHILDREN.

## Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

**Limited Warranty:** The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.