MATERIAL SAFETY DATA SHEET

For Coatings, Resins & Related Materials

Manufactured For: Kelly-Moore Paints Prep Date: 07/27/06

Address: 987 Commercial Street

San Carlos, CA 94070 Emergencies Involving Spills, Leaks, Fires, Exposure, Or Accident Contact

Product Class: Paint Thinner Chemtrec: 1-800-424-9300

Trade Name: KM-SA-65 Thinner

H.M.I.S. Codes: H F R P Information Phone: 1-888-677-2468

2* 3 0 -

Ingredient	C.A.S.#	Weight Percent	Occupt. Expos	sure Limits ACGIH TLV	Vapor Pressure mm Hg & Temp.F	
*4-Methyl 2-Pentanone	108-10-1	15-18	50 ppm	50 ppm	16	68
*Toluene	108-88-3	45-50	100 ppm	100 ppm	22	68
*Normal Butanol	71-36-3	12-16	50 ppm	50 ppm	4.4	68
*Methyl Ethyl Ketone	78-93-3	8-12	200 ppm	200 ppm	70	68
Diacetone Alcohol	123-42-2	4-8	50 ppm	50 ppm	16	68

^{*}Indicates toxic chemical(s) subject to reporting requirements of Section 313 of Title III and of 40 CFR 372.

Boiling Range (Deg. F): 175° Vapor Density: Heavier than air

Evaporation Rate: slower than Ether

Percent Volatile By Volume: 100 Weight Per Gallon (lbs.): 7.1

Flash Point (Deg. F): 20° Lower Explosive Limit: 1.2

Extinguishing Media: Foam, CO2, dry chemical, water fog

OSHA Flammability Classification: Flammable Liquid, Class IB

Special Firefighting Procedures: Wear a NIOSH/MSHA approved self contained breathing apparatus and full protective clothing. Use water to keep fire exposed containers cool. Water may be ineffective as an extinguishing agent.

Unusual Fire & Explosion Hazards: Vapors are heavier than air and may travel along the ground or be moved by ventilation to ignition sources at locations distant from material handling point. Pressure may build up in containers and create an explosion hazard. Never use welding or cutting torch on or near drum (even empty). Product and residue can ignite explosively.

KM-SA-65 Thinner

THIS PRODUCT IS FLAMMABLE

Effects Of Overexposure:

Eyes: Irritation, burning, tearing and redness.

Skin: Moderate irritation or defatting of skin upon prolonged or repeated contact.

Ingestion: Abdominal pain, nausea, vomiting and diarrhea.

Inhalation: Excessive exposure to vapors can cause headache, dizziness, uncoordination, nausea and

loss of consciousness.

Emergency & First Aid Procedures:

Eves: Flush with water for 15 minutes.

Skin: Remove contaminated clothing, wash skin with soap and water. **Ingestion:** Do not induce vomiting. Get medical attention immediately.

Inhalation: Move to fresh air, aid breathing if necessary.

In all cases, consult a physician for best treatment.

Chemical listed as carcinogen or potential carcinogen:

NTP: No IARC: No OSHA: No

Stability: Product Stable

Conditions to Avoid: All sources of ignition

Incompatibility (Materials to Avoid): Oxidizing agents, strong acids & bases

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, nitrogen oxides and organic

compounds.

Hazardous Polymerization: Will Not Occur

========= Section VII - SPILL OR LEAK PROCEDURES ============

Steps To Be Taken In Case Material Is Released Or Spilled: Dike spill area. Absorb spill with inert absorbent material. Place in sealed metal containers for proper disposal.

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations.

======== Section VIII - SPECIAL PROTECTION INFORMATION ========

Respiratory Protection: Use a NIOSH/MSHA jointly approved respirator

Ventilation: Use mechanical ventilation Protective Gloves: Neoprene or rubber Eye Protection: Chemical splash goggles

Other Protective Equipment: Protective clothing, barrier cream, eye bath, safety shower

Precautions To Be Taken In Handling & Storing; Store in dry area. Keep away from open flames and high temperatures.

Other Precautions: Minimize contact. Avoid breathing vapors. Practice good industrial hygiene and safe working practices.

State and Local Regulations:

California Proposition 65

This product contains the following substances known to the State of California to cause cancer, birth defects or other reproductive hazards: Benzene, Toluene