

Product Description

KM FAST DRY is a modified acrylic based sealant that offers unmatched paintability. **KM FAST DRY** allows you to spray paint immediately or brush/roll in only 30 minutes. Can be used on a wide variety of interior / exterior surfaces. **KM FAST DRY** will not crack or discolor paints. Forms a flexible, durable, airtight, water resistant seal offering exceptional protection from environmental conditions. Once cured, the bead is mildew resistant and exceeds the requirements of ASTM C-834 type OP, Grade -18°C.

Performance Features

- Spray Paint Immediately
- Brush or Roll in 30 Minutes
- Enhances Project Productivity
- No Call Backs
- Reduces Paint Film Cracking
- Will Not Discolor Paint
- 50 Year Limited Warranty

Compliance & Performance Certifications

- Exceeds ASTM C-834, Type OP, Grade -18°C

Product Specifications

Color:	White
Vehicle:	100% modified acrylic emulsion polymer
VOC Less water and exempts solvents:	< 1.5%
Solids:	Approx. 87%
Weight per gallon:	14.0 ± 0.5
Service temperature:	-25°F to 180°F
Temperature application range:	40°F minimum and rising. 140°F maximum.
Freeze thaw stability:	Passes 5 cycles @ 0°F (1 cycle = 16 hrs. @ 0°F 8 hrs. at 75°F)
Applications:	Interior / exterior
Shelf life:	24 months when stored at 50°F to 80°F
Coverage:	10.1 fl. oz.: 53 liner ft. at a 3/16" bead
Tooling time:	5 to 10 minutes
Paint over time:	Spray: Immediately Brush: 30 minutes
Tack free time:	30 minutes
Full cure:	7- 14 days

Surface Preparation

Surface to be caulked must be dry and free of all dirt, dust, oil, mildew, loose paint, old caulk or other contaminants. Only apply when sealant, surface and air temperatures are above 40°F and rising. Do not apply on surfaces that exceed 140°F, or when rain is expected.

Application

1. Cut nozzle at a 45° angle. Properly designed joint not to exceed 1/2" in width, use backer rod for joints deeper than 1/2".
3. Tool or smooth bead within 5 to 10 minutes, depending on climatic conditions. This is a fast dry formulation, for best results, tool immediately to ensure best adhesion and a smooth bead.
4. Spray paint immediately or allow 30 minutes curing time before applying paint by brush or roller.
5. Full cure should occur 7-14 days after application.
6. Clean up tools with soap and water.

Continued Next Page

KM FAST DRY - (cont.)

Clean Up

Clean all equipment immediately after use with warm, soapy water.

Precautions

DO NOT TAKE INTERNALLY

WARNING! IRRITATING TO SKIN, EYES AND RESPIRATORY TRACT. Harmful if swallowed, inhaled or absorbed through the skin. May cause allergic skin reactions and/or central nervous system depression. Adverse reproduction effects have been reported in animals. May cause adverse kidney effects. Avoid contact with eyes, skin and clothing. Use in well ventilated area. Wear eye, skin and respiratory protection. Eye contact: Immediately flush with water for 15 minutes and get medical attention immediately. If swallowed: Do not induce vomiting. Give large quantities of water and get medical attention. Never give anything by mouth to an unconscious person. For health information refer to Material Safety Data Sheet or call Chemtrec at 800-424-9300. **KEEP OUT OF REACH OF CHILDREN.**

⚠ **WARNING:** Cancer and Reproductive Harm - Go to www.P65Warnings.ca.gov for additional information

Material Safety Data Sheets (SDS) available upon request. Similar information for solvents and other chemicals used with Kelly-Moore products should be obtained from your supplier(s). When solvents are used, proper safety precautions must be observed.

FIRST AID: In case of skin contact, wash off quickly with plenty of soap and water, remove contaminated clothing. For eye contact flush eyes immediately with large quantities of water, for at least 15 minutes. Obtain emergency medical treatment. If swallowed, obtain medical treatment immediately. **DO NOT INDUCE VOMITING.** If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help.

Proper Disposal

Contact your local sanitation department or household hazardous waste coordinator for information concerning possible reuse or disposal of unused solvent-containing adhesives and / or sealants. All material must be disposed in accordance with Federal, State, and Local Regulations.

Durability Guarantee: After proper storage and application, if this product cracks, peels or separates within 50 years of installation, manufacturer will replace the product if purchaser returns proof of purchase to manufacturer. This shall be manufacturer's sole obligation with regard to this product and manufacturer shall not be liable for any damages, including incidental or consequential damages. This is the sole and exclusive remedy and liability for defects or failure of this product. MANUFACTURER HEREBY DISCLAIMS ALL WARRANTIES, WRITTEN OR ORAL, STATUTORY, EXPRESSED OR IMPLIED; INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS.