

SAFETY DATA SHEET

KM-275 103 WHITE

Page 1 – 8/23/2016

1. Product and Company Information

Product Name: KM-275 PART A BASE 103 WHITE
Company Name: Kelly Moore Paints
987 Commercial Street
San Carlos, CA 94070
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
Emergency Contact: CHEMTREC: (800) 424-9300

Phone Number:
1-888-677-2468

2. Hazards Identification

Target Organ Systemic Toxicity (repeated exposure), Category 2

Skin Sensitization, Category 1

Serious Eye Damage/Eye Irritation, Category 2A

Flammable Liquids, Category 3

Acute Toxicity: Skin, Category 4

Acute Toxicity: Inhalation, Category 4

Skin Corrosion/Irritation, Category 3

Aquatic Toxicity (Acute), Category 3



GHS Signal Word:

Danger

GHS Hazard Phrases:

H373 - May cause damage to organs through prolonged or repeated exposure.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H402 - Harmful to aquatic life.
H226 - Flammable liquid and vapor.
H312 - Harmful in contact with skin.
H332 - Harmful if inhaled.

GHS Precaution Phrases:

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash hands thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 - Use explosion-proof electrical/ventilating/lighting/ equipment.
P243 - Take precautionary measures against static discharge.
P242 - Use only non-sparking tools.
P271 - Use only outdoors or in a well-ventilated area.

GHS Response Phrases:

P314 - Get medical attention/advice if you feel unwell.
P302+352 - IF ON SKIN: Wash with plenty of soap and water.
P332+313 - If skin irritation occurs, get medical advice/attention.
P333+313 - If skin irritation or rash occurs, seek medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313 - If eye irritation persists, get medical advice/attention.
P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P312 - Call a POISON CENTER/doctor/if you feel unwell.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P501 - Contact a licensed professional waste disposal service to dispose of this material.
P403+235 - Store in cool/well-ventilated place.

GHS Storage and Disposal Phrases:

Potential Health Effects

(Acute and Chronic):

Inhalation:

Chronic inhalation may cause effects similar to those of acute inhalation.
May be harmful if inhaled. Causes respiratory tract irritation. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma.
Vapors may cause dizziness or suffocation.

KM-275 103 WHITE/PAGE 2

Skin Contact:	May be harmful if absorbed through the skin. Causes skin irritation. Prolonged and/or repeated contact may cause irritation and/or dermatitis. Causes redness and pain.
Eye Contact:	Causes severe eye irritation. Causes redness and pain.
Ingestion:	May be harmful if swallowed. May be harmful if inhaled. Causes respiratory tract irritation. May cause irritation of the digestive tract. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

3. Composition/Information on Ingredients

<u>CAS #</u>	<u>Hazardous Components (Chemical Name)</u>	<u>Concentration</u>
14808-60-7	Silicon Dioxide	30.0 - 40.0 %
25068-38-6	Bisphenol-a based epoxy resin	25.0 - 35.0 %
13463-67-7	Titanium dioxide	15.0 - 25.0 %
1330-20-7	Xylene (mixed isomers)	1.0 - 5.0 %
84852-15-3	Phenol, 4-Nonyl, branched	1.0 - 5.0 %
107-98-2	2-Propanol, 1-Methoxy-	1.0 - 5.0 %
100-41-4	Ethylbenzene	0.1 - 3.0 %

4. First Aid Measures

Emergency and First Aid Procedures	
In Case of Inhalation:	If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.
In Case of Skin Contact:	Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse.
In Case of Eye Contact:	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.
In Case of Ingestion:	Never give anything by mouth to an unconscious person. Rinse mouth with water.
Signs and Symptoms of Exposure:	Central nervous system depression. Dermatitis. Abdominal pain, Nausea. Vomiting, Anorexia. Shortness of breath.
Note to Physician:	Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media:	Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.
Fire Fighting Instructions:	Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable Liquid. Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.
Flammable Properties and Hazards:	Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air.

6. Accidental Release Measures

Steps To Be Taken In Case Material is Released Or Spilled:	Personal precautions. Use personal protective equipment. Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.
---	---

11. Toxicological Information

Toxicological Information:

Germ cell mutagenicity. Reproductive toxicity - no data available.
Aspiration hazard. Inhalation: May cause damage to organs through prolonged or repeated exposure.
Epidemiology: Teratogenicity: No information available.

Carcinogenicity/Other Information:

These products contain more than 0.1% crystalline silica (CAS #14808-60-7) which has been classified by IARC a Class 1 carcinogen. Normal application procedures pose no hazard since the silica is set and encapsulated, but grinding or sanding dried films may yield respirable silica dusts. Control exposures to less than 0.1 mg per cubic meter of air using approved dust filter respirators. Skin contact: Prolonged or repeated contact with product may cause slight skin irritation. Impervious gloves should be worn if prolonged skin contact is likely.

ACGIH Carcinogens

Quartz (CAS 14808-60-7) A2 Suspected human carcinogen

IARC Monographs, Overall Evaluation of Carcinogenicity 1 Carcinogenic to humans

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans

US NTP Report on Carcinogens: Known Carcinogen

Quartz (CAS 14808-60-7) Known to be human carcinogen

OSHA PEL: Exposure to airborne crystalline silica shall not exceed an 8 hour time weighted average limit as stated in 29CFR 1910.1000, Table-Z-1-A Air contaminants, specifically: Silica, Crystalline Quartz (Respirable) 0.1 MG/M3. ACGIH TLV-TWA: 01 MG/M3. NIOSH Maximum permissible conc. 0.05 MG/M3, 10 hour workday, 40 hour week. This product contains the following substances known to the State of California to cause cancer, birth defects, or other reproductive hazards: Benzene, Toluene, Crystalline Silica.

12. Ecological Information

General Ecological Information:

No data available

Persistence and Degradability:

No data available

Bioaccumulative Potential:

No data available

Mobility in Soil:

No data available

13. Disposal Considerations

Waste Disposal Method:

Dispose of as unused product. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT):

Consumer commodity – ORM-D – Used for 1 gallon containers when shipped in the United States of America
UN1263, Paint Related Material, 3, PG III – 5 Gallon pails

DOT Proper Shipping Name:



Marine Transport

IMDG Shipping:

UN1263, Paint Related Material, 3, PG III



AIR TRANSPORT (ICAO/IATA)

IATA Shipping Name:

UN1263, Paint Related Material, 3, PG III



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986.) Lists

<u>CAS #</u>	<u>Hazardous Components (Chemical Name)</u>	<u>S. 302 (EHS)</u>	<u>S. 304 RQ</u>	<u>S. 313 (TRI)</u>
14808-60-7	Silicon Dioxide	No	No	No
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes
13463-67-7	Titanium dioxide	No	No	No
84852-15-3	Phenol, 4-Nonyl-, Branched	No	No	No
100-41-4	Ethylbenzene	No	Yes 1000 LB	Yes
107-98-2	2-Propanol, 1-Methoxy-	No	No	No

V.O.C. (WHITE) 1.56 LBS/GAL. (187 GMS/L)

16. Other Information

Revision Date: 8/23/2016

Additional Information About this Product:

Hazardous Material Information System III (U.S.A)

Health: 2*

Flammability: 3

Reactivity: 0

Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Kelly Moore Paint Co., and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.