

SAFETY DATA SHEET

KM-370 103 WHITE

Page 1 – 8/29/2016

1. Product and Company Information

Product Name: KM-370 PART A BASE 103 WHITE
Company Name: Kelly Moore Paints
987 Commercial Street
San Carlos, CA 94070
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
Emergency Contact: CHEMTREC: (800) 424-9300

Phone Number:
1-888-677-2468

2. Hazards Identification

Skin Corrosion/Irritation, Category 3
Flammable Liquids, Category 3
Toxic To Reproduction, Category 1B
Aquatic Toxicity (Acute), Category 3
Target Organ Systemic Toxicity (single exposure), Category 3



GHS Signal Word: **Danger**

GHS Hazard Phrases: H316 - Causes mild skin irritation.
H226 - Flammable liquid and vapor.
H402 - Harmful to aquatic life.
H335 - May cause respiratory irritation.

GHS Precaution Phrases: P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P241 - Use explosion-proof electrical/ventilating/lighting/equipment.
P243 - Take precautionary measures against static discharge.
P242 - Use only non-sparking tools.
P281 - Use personal protective equipment as required.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 - Use only outdoors or in a well-ventilated area.

GHS Response Phrases: P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P332+313 - If skin irritation occurs, get medical advice/attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313 - If eye irritation persists, get medical advice/attention.
P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.
P403+235 - Store in cool/well-ventilated place. Store locked up.
P501 - Contact a licensed professional waste disposal service to dispose of this material.

GHS Storage and Disposal: Chronic: Prolonged or repeated skin contact may cause defatting and dermatitis.

Potential Health Effects (Acute and Chronic):

Inhalation: Material is irritating to mucous membranes and upper respiratory tract. Harmful if inhaled. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Vapors may cause dizziness or suffocation.

Skin Contact: May be harmful if absorbed through the skin. Prolonged and/or repeated contact may cause irritation and/or dermatitis.

KM-370 103 WHITE/PAGE 2

Eye Contact:

Causes eye irritation. Causes redness and pain.

Ingestion:

May be harmful if swallowed. May be harmful if inhaled.

May cause irritation of the digestive tract. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

3. Composition/Information on Ingredients

| <u>CAS #</u> | <u>Hazardous Components (Chemical Name)</u> | <u>Concentration</u> |
|--------------|---------------------------------------------|----------------------|
| Proprietary | Acrylic Polymer Resin | 30.0 - 40.0% |
| 13463-67-7 | Titanium dioxide | 30.0 - 40.0% |
| 108-65-6 | Propylene glycol methyl ether acetate | 20.0 - 30.0% |
| 123-86-4 | Butyl Acetate | 5.0 - 15.0% |

4. First Aid Measures

Emergency and First Aid Procedures

In Case of Inhalation:

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.

In Case of Skin Contact:

Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.

In Case of Eye Contact:

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion:

Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Get medical aid.

Signs and Symptoms of Exposure:

Central nervous system depression. Dermatitis. Abdominal pain, Nausea, Vomiting, Anorexia. Shortness of breath.

Note to Physician:

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media:

Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Fire Fighting Instructions:

Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable Liquid. Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

Flammable Properties and Hazards:

Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled:

Personal precautions.
Use Personal protective equipment.
Spills/Leaks: Control runoff and isolate discharged material for proper disposal.
Use water spray to cool and disperse vapors and protect personnel.

KM-370 103 WHITE/PAGE 3

7. Handling and Storage

Precautions To Be Taken in Handling:

Avoid contact with skin and eyes. Normal measures for preventive fire protection. Avoid inhalation of vapor or mist.

Precautions To Be Taken in Storing:

Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Suitable: Keep away from heat, sparks, and open flame.

8. Exposure Controls/Personal Protection

| <u>CAS #</u> | <u>Partial Chemical Name</u> | <u>OSHA TWA</u> | <u>ACGIH TWA</u> |
|--------------|---------------------------------------|----------------------------------|-------------------------------|
| Proprietary | Acrylic Polymer Resin | N/E | N/E |
| 13463-67-7 | Titanium Dioxide | PEL: 15 (dust) mg/m ³ | TLV: 10 mg/m ³ |
| 108-65-6 | Propylene glycol methyl ether acetate | N/E | N/E |
| 123-86-4 | Butyl acetate | PEL: 150 PPM | TLV: 150 PPM STEL: 200 PPM |

Respiratory Equipment (Specify Type):

For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

Eye Protection:

Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves:

Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls

(Ventilation, etc):

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Work/Hygienic/Maintenance Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

| | | | |
|--------------------------------|-------------------|--------------|-----------|
| Physical States: | [] Gas | [X] Liquid | [] Solid |
| Flash Point: | 81 ° F | | |
| Boiling Point: | 250° F | | |
| Explosive Limits: | LEL: 1.2 | UEL: 7.5 | |
| Weight Per Gallon: | 11.75 +/- .3 | | |
| Vapor Pressure (mm Hg): | 8.4 @ 68 | | |
| Vapor Density: | Heavier than Air | | |
| Evaporation Rate: | Slower than Ether | | |
| Percent Volatile: | 36 (VOL) | | |

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions to Avoid - Heat, flames and sparks:

Instability:

Incompatibility – Materials Bases, Strong oxidizing agents

To Avoid

Hazardous Decomposition or Nature of decomposition products unknown.

Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions to Avoid - No data available.

Hazardous Reactions:

11. Toxicological Information

Toxicological Information: Epidemiology: No information found.
Teratogenicity: Exposure to n-butyl acetate vapors throughout gestation did not cause significant teratogenicity in rabbits, rats, or mice.

**Irritation or Corrosion:
Carcinogenicity/Other
Information:** NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

12. Ecological Information

**General Ecological
Information:** No data available.
**Persistence and
Degradability:** No data available.
Bioaccumulative Potential: No data available.
Mobility in Soil: No data available.

13. Disposal Considerations

Waste Disposal Method: Dispose of as unused product. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT): Consumer commodity – ORM-D – Used for 1 gallon containers when shipped in the United States of America
DOT Proper Shipping Name: UN1263, Paint Related Material, 3, PG III – 5 Gallon pails



**Marine Transport
IMDG Shipping:** UN1263, Paint Related Material, 3, PG III



AIR TRANSPORT (ICAO/IATA): UN1263, Paint Related Material, 3, PG III
IATA Shipping Name:



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

| <u>CAS #</u> | <u>Hazardous Components (Chemical Name)</u> | <u>S. 302 (EHS)</u> | <u>S. 304 RQ</u> | <u>S. 313 (TRI)</u> |
|--------------|---------------------------------------------|---------------------|------------------|---------------------|
| Proprietary | Acrylic Polymer Resin | No | No | No |
| 13463-67-7 | Titanium dioxide | No | No | No |
| 108-65-6 | Propylene glycol methyl ether acetate | No | No | No |
| 123-86-4 | Butyl acetate | No | Yes 5000 LB | No |

V.O.C. (mixed) 2.70 LBS/GL (323 GMS/L)

16. Other Information

Revision Date: 8/29/2016

Additional Information about this Product:

Hazardous Material Information System III (U.S.A)

Health: 2

Flammability: 3

Reactivity: 0

Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Kelly Moore Paint Co., and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.