

PRODUCT DESCRIPTION

Kelly-Moore Color Samples are premium quality interior/exterior low sheen paints designed to duplicate most colors in the Kelly-Moore color system.

SUBSTRATES & SYSTEM RECOMMENDATIONS

PREPARATION Properly prepare all new or previously painted surfaces. See 'Surface Preparation' below for detailed instructions.

SUBSTRATES This product is not intended for use as a primer or finish coat. It can be applied over prepared drywall, plaster, masonry, metal, wood and hardboard. See 'Application' on Page 2 for specifications.

FULL COLOR Two coats are required to achieve full color representation. Color may vary slightly from the final finish chosen. Sheen variance and light reflection will affect perceived color.

SYSTEM RECOMMENDATIONS Kelly-Moore offers a wide variety of paints in many sheens for nearly every surface. It is important to choose the correct product for your project. Ask your local Kelly-Moore representative for the appropriate system recommendation.

BEFORE YOUR PROJECT Be sure to scuff sand and prime any surfaces painted with color samples. This will help prevent any difference in sheen or color over tested areas. It is important to start your project with a uniform surface.

SPECIFICATIONS**RESIN TYPE**

100% Acrylic

FINISH

Low Sheen <10 @ 60°

SIZES AVAILABLE

Quart Containers

BASES AVAILABLEWhite &
Custom Tinted Colors**WEIGHT PER GALLON**

11.1 ± 0.25 lbs.

SOLIDS BY VOLUME

39% ± 2%

TEMPERATURE

50°F - 100°F

FILM THICKNESS4.0 - 6.0 Wet Mills
1.6 - 2.3 Dry Mills**PRACTICAL
COVERAGE**

250-400 sq ft/gal

DRYING TIME@ 75°F & 50% R.H.
Touch: 2 Hours
Recoat: 4 Hours**CLEAN-UP**

Soapy Water

V.O.C.<50 g/L
(per ASTM D6886)**MEETS V.O.C.
LIMITS FOR**

- CARB
- National AIM
- SCAQMD
- Green Seal GS-11
- LEED V4

SURFACE PREPARATION

GENERAL All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces.*

NEW SURFACES All surfaces should be sound, free of contamination and dry. Wood surfaces should be sanded free of wood fibers. Wood should have a moisture content of less than 15% as measured by a moisture meter. Masonry and plaster should be thoroughly cured before priming. Masonry should have a moisture content of less than 12% as measured by a moisture meter.

NEW FERROUS METAL Follow general surface preparation guidelines. Remove all loose rust, mill scale, or deteriorated previously applied coatings by Hand Tooling (SSPC-SP-2) or Power Tool Cleaning (SSPC-SP-3).

NEW ALUMINUM & GALVANIZED METAL Wash thoroughly with TSP or other suitable cleaner/degreaser to remove oil and other contaminants. Rinse thoroughly.

PREVIOUSLY PAINTED SURFACES Remove any peeling, chalky or loosely adhering paint, sand to feather edges, dust clean (do not use tack rags). Sand glossy finishes.*

*See WARNING! on Page 2 for existing leaded paint.

KELLY-MOORE PAINT COMPANY INC.
987 COMMERCIAL ST. SAN CARLOS, CA 94070

APPLICATION

MIXING Mix well before use. Purchase enough paint to complete your project at the same time. If additional paint is needed, retain some of the original material and intermix the paint before application.

THINNING Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

DRYING Dry times are based on standard conditions of 75°F with a relative humidity of 50%. Lower temperatures or higher humidity may extend drying times. Higher temperatures may speed drying time. Provide adequate ventilation and air movement during and after painting.

TEMPERATURE Do not apply when material, air, and/or surface temperature is outside of the recommendations on page 1. Store at room temperature and protect from freezing.

COVERAGE May vary depending on method of application, porosity and texture of the surface.

NEW SURFACES Prime surfaces following primer recommendations on Page 1 and 2.

Two finish coats will provide a more even color and sheen. It will also help with touch-up and durability. Backroll while spraying to ensure an even coat. Backrolling the prime coat will fill in porous surfaces. Backrolling the topcoat will reduce pinholes, create uniform sheen, and make for easier touch-up. Avoid lap marks by maintaining a wet edge at all times. Re-wet your applicator before it starts to run dry; any light spots, when dried, may appear different than heavy spots in both color and sheen. An even coat is your goal. Lay the paint on and leave it alone. Be sure to give paint an opportunity to flow and level after application. This product is not intended for use on floors.

PREVIOUSLY PAINTED SURFACES Glossy surfaces should be completely dulled prior to painting. Spot prime bare and patched areas or prime entire surface with a suitable Kelly-Moore product. When making a significant color change, a primer is recommended to aid hide and appearance of the finish coating. Follow application instructions for 'new surfaces' listed above.

SAFETY INFORMATION

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information consult the Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION

KEEP OUT OF REACH OF CHILDREN

For proper disposal of excess material, please contact your local city or county waste management agency.

WARNING!

If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1- 800-424-LEAD (5323) or log on to www.epa.gov/lead.

LIMITED WARRANTY

The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.