

1. Identification

Product identifier	550 AcryPlex Interior Flat Paint Stock Colors	
Other means of identification		
Product code	550 (014, 023, 027, 036)	
Recommended use	Architectural Coating	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Company name	Kelly-Moore Paint Co., Inc.	
Address	1390 El Camino Real, Third Floor San Carlos, CA 94070, USA	
Email	TAlvarez@kellymoore.com	
Contact person	Tiffany Alvarez Gonda	
Telephone	1-800-874-4436	
Emergency telephone	CHEMTREC: 1-800-424-9300	

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Sensitization, skin	Category 1
	Carcinogenicity (inhalation)	Category 2
	Reproductive toxicity	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction. Suspected of causing cancer by inhalation. Suspected of damaging fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	< 23
Kaolin	1332-58-7	< 10
Aluminum hydroxide	21645-51-2	< 2

Chemical name	CAS number	%
Kaolin, calcined	92704-41-1	< 2
Silicon dioxide, crystalline silica-free	7631-86-9	< 2
Trimethylolpropane	77-99-6	< 0.3
2-Methyl-2H-isothiazol-3-one	2682-20-4	< 0.1

All concentrations are in percent by weight (kg) unless ingredient is a gas. Gas concentrations are in percent by volume (l).

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This product is miscible in water. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

Components

Type

Value

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

TWA

80 mg/m³

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components

Type

Value

Form

Kaolin (CAS 1332-58-7)

PEL

5 mg/m³

Respirable fraction.

15 mg/m³

Total dust.

Titanium dioxide (CAS 13463-67-7)

PEL

15 mg/m³

Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components

Type

Value

Form

Kaolin (CAS 1332-58-7)

TWA

5 mg/m³

Respirable fraction.

15 mg/m³

Total dust.

50 mppcf

Total dust.

15 mppcf

Respirable fraction.

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

TWA

20 mppcf

US. ACGIH Threshold Limit Values

Components

Type

Value

Form

Aluminum hydroxide (CAS 21645-51-2)

TWA

1 mg/m³

Respirable fraction.

Kaolin (CAS 1332-58-7)

TWA

2 mg/m³

Respirable fraction.

Titanium dioxide (CAS 13463-67-7)

TWA

10 mg/m³

US. NIOSH: Pocket Guide to Chemical Hazards

Components

Type

Value

Form

Kaolin (CAS 1332-58-7)

TWA

5 mg/m³

Respirable.

10 mg/m³

Total

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

TWA

6 mg/m³

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Skin protection

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	Milky white to colored liquid.
Physical state	Liquid.
Form	Liquid.
Color	Various.
Odor	Slightly ammoniacal.
Odor threshold	Not available.
pH	7 - 10
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	< 1 (n-BuAc=1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	> 1 (Air=1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Moderately soluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	45.017 - 45.348 g/L

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Strong acids.
Hazardous decomposition products	Carbon oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Suspected of causing cancer by inhalation. Prolonged inhalation may be harmful.
-------------------	---

Skin contact May cause an allergic skin reaction.
Eye contact Direct contact with eyes may cause temporary irritation.
Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
------------	---------	--------------

Aluminum hydroxide (CAS 21645-51-2)

Acute

Oral

LD50	Rat	> 5000 mg/kg
------	-----	--------------

Kaolin (CAS 1332-58-7)

Acute

Dermal

LD50	Rat	> 5000 mg/kg
------	-----	--------------

Inhalation

LC50	Rat	> 2 mg/l, 4 Hours
------	-----	-------------------

Oral

LD50	Rat	> 5000 mg/kg
------	-----	--------------

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Acute

Dermal

LD50	Rabbit	> 5000 mg/kg, 24 Hours
------	--------	------------------------

Inhalation

Dust

LC50	Rat	> 0.14 mg/l, 4 Hours
------	-----	----------------------

Oral

LD50	Rat	> 3300 mg/kg
------	-----	--------------

Titanium dioxide (CAS 13463-67-7)

Acute

Oral

LD50	Rat	> 5000 mg/kg
------	-----	--------------

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer by inhalation.

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Kaolin (CAS 1332-58-7)		
Aquatic		
<i>Acute</i>		
Crustacea	LC50	Daphnia magna
		> 1.1 g/l, 48 Hours
Titanium dioxide (CAS 13463-67-7)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna
		> 100 mg/l, 48 Hours
Fish	LL50	Oryzias latipes
		> 100 mg/l, 96 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil The product is water soluble and may spread in water systems.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components on the TSCA 8(b) inventory are designated "active" or are exempt from reporting under the Inventory Update Rule.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories Respiratory or skin sensitization
Carcinogenicity
Reproductive toxicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Kaolin (CAS 1332-58-7)
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)
Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Kaolin (CAS 1332-58-7)
Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Kaolin (CAS 1332-58-7)
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)
Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Kaolin (CAS 1332-58-7)
Titanium dioxide (CAS 13463-67-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1)	Listed: January 1, 1988
Acetaldehyde (CAS 75-07-0)	Listed: April 1, 1988
Benzene (CAS 71-43-2)	Listed: February 27, 1987
Carbon black (CAS 1333-86-4)	Listed: February 21, 2003
Cumene (CAS 98-82-8)	Listed: April 6, 2010
Dichloromethane (CAS 75-09-2)	Listed: April 1, 1988
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
Ethylene oxide (CAS 75-21-8)	Listed: July 1, 1987
Formaldehyde (CAS 50-00-0)	Listed: January 1, 1988
Methyloxirane (CAS 75-56-9)	Listed: October 1, 1988
Silica, Crystalline (airborne particles of respirable size) (CAS 14808-60-7)	Listed: October 1, 1988
Titanium dioxide (CAS 13463-67-7)	Listed: September 2, 2011

California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997
Ethylene oxide (CAS 75-21-8)	Listed: August 7, 2009
Methanol (CAS 67-56-1)	Listed: March 16, 2012
Toluene (CAS 108-88-3)	Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

Issue date 08-October-2021

Revision date -

Version # 01

HMIS® ratings Health: 2*
Flammability: 1
Physical hazard: 0

Disclaimer Kelly-Moore Paint Co., Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.