

PRODUCT DESCRIPTION

Epic is a line of super-premium interior and exterior enamels designed for use on trim and accent areas where a smooth, self-leveling, and durable finish is desired. Created with a unique urethane-alkyd resin to provide a long lasting finish that out performs standard enamel coatings. This user friendly, waterborne formulation is ideal for residential, commercial, and light industrial applications. Epic can be used on masonry, metal, wood and hardboard. An excellent choice for moldings, doors, railings, construction equipment, storage containers, structural steel, and much more.

FEATURES & SPECIFICATIONS

PERFORMANCE FEATURES

- Ultra-Smooth Finish
- Self-Leveling
- Excellent Durability
- Resists Yellowing
- Water Clean-Up
- Lifetime Warranty

MEETS VOC LIMITS

- ✓ CARB
- ✓ SCAQMD
- ✓ National AIM
- ✓ LEED v4
- ✓ GS-11

AVAILABLE PRODUCTS

FINISHES:

- 1997 Satin 20 - 35 @ 60°
- 1998 Semi-Gloss 55 - 65 @ 60°
- 1999 Gloss 85+ @ 60°

BASES & COLORANT:

- 121 White 0 - 2 oz/gal
- 222 Medium 1.5 - 4 oz/gal
- 333 Deep 4 - 8 oz/gal
- 555 Neutral 8 - 12 oz/gal

STOCK COLORS: Swiss Coffee

SIZES: Gallon & Five Gallon

Available finish, base, & size combinations may vary.

PRODUCT SPECIFICATIONS

RESIN TYPE: Urethane Alkyd

VOC (ASTM D6886): < 50 g/L

SOLIDS BY VOLUME:

- Satin 39 ± 2%
- Semi-Gloss 38 ± 2%
- Gloss 40 ± 2%

WEIGHT PER GALLON:

- Satin 11.4 ± .25 lbs.
- Semi-Gloss 11.1 ± .25 lbs.
- Gloss 10.9 ± .25 lbs.

SUBSTRATES & SYSTEM RECOMMENDATIONS

PREP: All surfaces must be cured, firm and dry. Use a suitable cleaner to remove all dirt, oil or other contamination. Sand glossy surfaces and remove dust. (See WARNING!)

PRIME: 1 Coat - Recommended Primer

Interior

- Drywall & Masonry:** 971 AcryPlex PVA
- Wood & Hardboard:** 973 AcryPlex Wood
- Metal:** 5725 DTM Primer/Finish

Previously Painted: 295 Kel-Bond Universal or apply topcoat directly over prepared surface.

Exterior

- Masonry & Stucco:** 247 AcryShield Masonry
- Wood & Hardboard:** 255 AcryShield Wood
- Metal:** 5725 DTM Primer/Finish

PAINT: 2 Coats - Epic

- Brush:** Synthetic Bristle
- Roll:** 3/8"-3/4" Synthetic Cover
- Spray:** 2000-2500 PSI / .013"-.019" Tip
- Thickness:** 4-6 Mills Wet / 1.6-2.4 Mills Dry
- Coverage:** 250-400 sq/ft Per Gallon

- Temperature:** 50°F - 100°F
- Dry Time:** 4 Hours Touch / 24 Hours Recoat
- Clean-up:** Water
- Thinning:** Not Required / <10% Water, If Necessary

ENVIRONMENT, FILM THICKNESS, AND RECOAT: Always follow recommendations for application weather conditions, moisture content, film thickness, and recoat times. Application outside of recommendations may reduce performance and can lead to extended dry times, improper cure or a soft film.

See following pages for detailed preparation and application instructions.

KELLY-MOORE PAINT COMPANY INC.

HURST, TEXAS 76053 USA

PREPARATION & APPLICATION**BEFORE PAINTING**

GENERAL PREPARATION: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces. (See WARNING!)

NEW FERROUS METAL: Remove all loose rust, mill scale, or deteriorated previous coatings by Hand Tooling (SSPC-SP-2) or Power Tool Cleaning (SSPC-SP-3).

NEW ALUMINUM & GALVANIZED METAL: Wash surface with TSP or other suitable cleaner, degreaser, or etching solution to remove oil and contaminants. Rinse thoroughly.

TANNIN RICH WOOD: Allow to weather until tannins naturally come out of the substrate. Clean tannins from surface prior to priming and painting.

NEW & BARE SURFACES: Prime surfaces following recommendations on page 1 & 2.

PREVIOUSLY PAINTED SURFACES: Remove any peeling, chalky or loosely adhering paint, sand to feather edges, dust clean (do not use tack rags). Glossy surfaces should be completely dulled prior to painting. (See WARNING!) Spot prime bare and patched areas or prime entire surface with a suitable Kelly-Moore product. When making a significant color or sheen change, a primer is recommended to aid hide and appearance of the topcoat.

MOISTURE: All surfaces should be dry before painting. Wood should have an internal moisture content of less than 15%. Masonry and plaster should be thoroughly cured and have an internal moisture content of less than 12%.

STAIN BLOCKING: When painting over stains or tannins, an appropriate primer is recommended before top coating. For heavy stains, a second coat of primer may be required. 24 hours are required between all coats.

PATCHING & CAULKING: Prime the surface then apply paintable patching or siliconized acrylic caulking to the manufacturer's recommendations. Patching should be reprimed once dry. Caulking should be allowed to fully dry, then the finish paint applied. Using fast dry primers over caulking is not recommended. Elastomeric patch & caulking are recommended with elastomeric paints only. Painting over flexible patch or caulking or in areas with substrate movement may cause cracking of the topcoat.

MIXING: Mix well before use. Purchase enough paint to complete your project at the same time. If additional paint is needed, retain some of the original material and intermix the paint before application or touch up.

THINNING: Apply at can consistency. If thinning is necessary to maintain workability, do not exceed 10%.

CONTAINERS AND TOOLS: Transfer material into a clean container for use. Use new or thoroughly cleaned tools. To avoid contamination, do not re-dip applicators or add used material into containers being used for storage.

DURING PAINTING

GENERAL PAINTING: Apply two separate finish coats to create even color, uniform sheen, maximum durability and easier touch-up. Maintain a wet edge while painting.

TESTING: Prior to full application, apply a test patch to ensure the preparation and coating system are appropriate for the project. If test patch results do not meet the needs of the project, contact a Kelly-Moore representative for recommendations.

COVERAGE: May vary depending on method of application, porosity and texture of the surface.

FILM THICKNESS: Always follow recommendations for application thickness on page 1. Over application may reduce performance and can lead to runs, extended dry times or a soft film.

WEATHER: Apply product only when material, air, and surface temperature are within the recommendations on page 1 and will remain above that temperature for at least 24 hours. Temperatures must remain 5° above the dew point during application and dry time. Do not expose to rain, fog, snow or any moisture during application or dry time. Limit exposure to heavy moisture for 24-48 hours after application.

BACKROLLING: While spraying, follow with a wet roller to ensure an even coat and fill in porous surfaces. This will reduce pinholes, create uniform sheen and make for easier touch-up.

FIBER CEMENT BOARD: Prime bare or factory primed surfaces. A minimum of two finish coats are required for sheen uniformity and touch up. Backroll all spray applied coats for best results.

RECOATING: Always follow recommendations for recoat times on page 1. Recoating too soon or too long after painting may reduce performance and can lead to adhesion loss, improper cure or a soft film.

AFTER PAINTING

DRYING: Dry times are based on standard conditions of 75°F with a relative humidity of 50%. Lower temperatures or higher humidity may extend drying times. Higher temperatures may speed drying time. Provide adequate ventilation and air movement during and after painting.

STORAGE: Store material at room temperature in a clean, tightly sealed container free of rollers, brushes, or other outside materials. Protect from freezing.

CURE: Architectural paints require up to 30 days after final application for full cure and maximum performance. Cure times vary depending on environmental conditions and air circulation.

CLEANING: Wait until at least two weeks after final paint application. Clean with fresh water and a cotton cloth. A small amount of mild detergent can be used, if necessary. See Kelly-Moore's Maintaining Painted Surfaces guide for more information.

SPECIALTY PRIMER RECOMMENDATIONS**Stain Blocking / Color Change**
295 Kel-Bond Universal**Tannin Rich Wood**
265 Hybrid**Chalky Surfaces**
98 Multi-Seal**Rough Surfaces**
285 Kel-Bond Ultra**Porous Masonry**
521 Block Filler**Dense or Glossy Surfaces**
287 Kel-Bond Plus

Ask a local Kelly-Moore representative for additional system recommendations.

SAFETY INFORMATION**CAUTION!**

Harmful if inhaled. Causes eye, nose, throat and lung irritation. Overexposure may cause lung damage. Close container after each use. Keep away from heat and flame.

Do not breath dust, vapors or spray mist. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1- 800-424-LEAD (5323) or log on to www.epa.gov/lead.

Satin (1998)

 **WARNING** Cancer - www.P65Warnings.ca.gov/product

Semi-Gloss (1998), Gloss (1999)

 **WARNING** Cancer and Reproductive Harm- www.P65Warnings.ca.gov/product

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

DO NOT TAKE INTERNALLY
USE ONLY WITH ADEQUATE VENTILATION
KEEP OUT OF REACH OF CHILDREN

SEE THE SAFETY DATA SHEET (SDS) FOR ADDITIONAL HEALTH AND SAFETY INFORMATION

LIFETIME LIMITED WARRANTY

Subject to the limitations set forth in this Technical Data Sheet, Kelly-Moore Paint Company, Inc. (“KM”) warrants that the Epic Interior / Exterior Paint product (the “Product”) shall be free from peeling, blistering and cracking defects during the Lifetime (as hereinafter defined) (the “Lifetime Limited Warranty”). This Lifetime Limited Warranty applies to and requires the painting of properly-prepared exterior surfaces with one (1) coat of the appropriate KM primer followed by two (2) separate coats of the Product by the owner (“Owner”) or his/her/its contractor on the structure. For the purpose of this Lifetime Limited Warranty, the term “Lifetime” means and refers to that period commencing on the date of application of the Product on the structure until such time that the Owner conveys, assigns, sells or transfers the structure on which the Product has been applied (the “Warranty Period”). This Lifetime Limited Warranty is non-transferrable and non-assignable. All recommendations for surface preparation and application made on this Technical Data Sheet must be strictly followed in order for the Lifetime Limited Warranty to be valid. If KM verifies that the Product peels, blisters or cracks during the Warranty Period due to a defect of the Product, Owner’s sole and exclusive remedy shall be KM’s replacement, at no additional cost to Owner, of an adequate quantity of the Product required to repair the affected portions of the subject surfaces to a sound condition. Owner shall not be entitled to any other remedy in lieu of Product replacement. KM does not warrant the film integrity of previously applied coatings. This Lifetime Limited Warranty does not apply to improperly prepared or below grade surfaces, surfaces not specifically recommended for coating application or coating failures resulting from cracks or openings, structural defects, faulty construction, physical abuse, extreme weather, natural disasters or other causes beyond KM’s reasonable control. Color fading is specifically excluded from this Lifetime Limited Warranty. This Lifetime Limited Warranty excludes labor and the cost of labor. No modifications, changes or amendments to this Lifetime Limited Warranty are valid. THE LIFETIME LIMITED WARRANTY STATED IN THIS TECHNICAL DATA SHEET IS EXCLUSIVE OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, STATUTORY, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, NONE OF WHICH SHALL APPLY TO THE PRODUCT. TO THE MAXIMUM EXTENT PERMITTED UNDER THE LAW OF THE JURISDICTION WHERE THE PRODUCT IS SOLD, THIS WARRANTY ALSO EXCLUDES LIABILITY FOR ANY LOSS OF PROFITS, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR BREACH OF ANY LIFETIME LIMITED WARRANTY ON THE PRODUCTS. KM SHALL NOT BE LIABLE FOR ANY LOSS, CLAIM, EXPENSE OR DAMAGE CAUSED BY, CONTRIBUTED TO OR ARISING OUT OF THE ACTS OR OMISSIONS OF OWNER OR THIRD PARTIES, WHETHER NEGLIGENT OR OTHERWISE. IN NO EVENT SHALL KM’S LIABILITY UNDER ANY CAUSE OF ACTION WHATSOEVER EXCEED THE COST OF THE PRODUCT GIVING RISE TO THE CLAIM, WHETHER BASED IN CONTRACT, WARRANTY, INDEMNITY OR TORT (INCLUDING NEGLIGENCE AND STRICT LIABILITY) OR OTHERWISE.