

Kel-Pro is Kelly-Moore's production quality line of zero VOC interior paints. Available in flat and enamels, Kel-Pro offers a solution for just about any interior project. Formulated to be fast drying and provide excellent uniformity and touch up abilities.

Kel-Pro 705 Interior Flat possesses non-bridging properties, making this product ideal for acoustic tile surfaces and a wide variety of commercial and residential applications.

Kel-Pro is available in one and five gallon containers and can be tinted to an assortment of designer colors. Kel-Pro is the product of choice for the painting professional when performance and economics are a must.

Kel-Pro is available in five designer sheens:

705 Kel-Pro Interior Flat

Conforms to Green Seal GS-11 Criteria

710 Kel-Pro Interior Low Sheen

Conforms to Green Seal GS-11 Criteria

715 Kel-Pro Interior Eggshell

Conforms to Green Seal GS-11 Criteria

720 Kel-Pro Interior Satin

Conforms to Green Seal GS-11 Criteria

750 Kel-Pro Interior Semi-Gloss

Conforms to Green Seal GS-11 Criteria



	705	710	715	720	750
FINISH MPI GLOSS LEVEL	Flat MPI Gloss Level 1	Low-Sheen MPI Gloss Level 2	Eggshell MPI Gloss Level 3	Satin MPI Gloss Level 4	Semi-Gloss MPI Gloss Level 5
SHEEN	< 3 @ 60 Degrees	5-7 @ 60 Degrees	10-15 @ 60 Degrees	30-40 @ 60 Degrees	45-55 @ 60 Degrees
WEIGHT/ GALLON	11.2 lbs	11 lbs	10.05 lbs	10.1 lbs	9.7 lbs
SOLIDS BY WEIGHT	50.92%	43.68%	41.89%	40.67%	38.07%
SOLIDS BY VOLUME	31.29%	32.38%	31.16%	31.09%	29.64%
RESIN TYPE	Co-Polymer				
DRY TO TOUCH (75° F & 50% RH)	30 Minutes				
DRY TO RECOAT (75° F & 50% RH)	4 Hours				
PRACTICAL COVERAGE	250-350 Sq. Ft/Gal				
RECOMMENDED DFT	1.6 -2.0 Mils / Coat				
VOC	Zero				
SHELF LIFE	2 years (unopened)				
COLOR RANGE	White, Custom Colors				
SIZES	One Gallon & 5 Gallon				
CLEAN UP	Water				
SPECIFIED PRIMERS	971 PVA Sealer / 295 Universal Primer				
APPLICATION	  				