

SAFETY DATA SHEET

Date of issue/Date of revision 4-24-2018

Version 1

Section 1. Identification

Product name : KM50 BONE 10.1OZ SILICONIZED ACRYLIC
Product code : KM-01009
Other means of identification : Caulk, Sealant
Product type : Paste

Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications.
Use of the substance/ mixture : Caulking, Sealing
Uses advised against : Not applicable.

Supplier : Tower Sealants
 2095 Memorial Park Road
 Gainesville, GA 30504

Emergency telephone number : Chemtrec: 1-800-424-9300

Technical Phone Number : 1-770-535-8782 (8:00 am to 5:00 pm EST)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : CARCINOGENICITY - Category 1A

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 72.5%

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : May cause eye irritation
 : May cause Cancer
 : May cause genetic defects
 : May cause damage to organs through prolonged exposure.

Precautionary statements

Product code KM-01009

Date of issue 4-24-2018

Version 1

Product name KM50 BONE 10.1OZ SILICONIZED ACRYLIC

Section 2. Hazards identification

- General** : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
- Response** : IF exposed or concerned: Get medical attention.
- Storage** : Store locked up.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : Sanding and grinding dusts may be harmful if inhaled. This product contains Crystalline Silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Since this product is not meant to be sanded or sprayed, risk of exposure is considered low. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.
- Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Product name** : KM50 BONE 10.1OZ SILICONIZED

Ingredient name	%	CAS number
Limestone	30 - 60	1317-65-3
Titanium Dioxide	1 - 6	13463-67-7
Acetaldehyde	0.1 - 1	75-07-0
Vinyl Acetate	0.1 - 1	108-05-4
Crystalline Silica, respirable powder (<10 microns)	0.1 - 1	14808-60-7
Ethylene Glycol	0.5 - 1.5	107-21-1

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Section 4. First aid measures

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Direct contact may cause slight to moderate irritation.
Inhalation : May cause slight irritation to respiratory passages – headache – dizziness.
Skin contact : May cause allergic skin reactions and / or central nervous system depression.
Ingestion : No known significant effects or critical hazards. Low ingestion hazard.

Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments : No specific treatment.
Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

Section 5. Fire-fighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Section 7. Handling and storage

- Special precautions** : If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Limestone	OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust
Titanium Dioxide	OSHA PEL (United States, 2/2013). TWA: 15 mg/m ³ 8 hours. Form: Total dust
Acetaldehyde	ACGIH TLV (United States, 6/2013). TWA: 10 mg/m ³ 8 hours.
Vinyl Acetate	ACGIH TLV (United States, 6/2013). C: 45 mg/m ³ C: 25 ppm
Crystalline Silica, respirable powder (<10 microns)	OSHA PEL (United States, 2/2013). TWA: 360 mg/m ³ 8 hours. TWA: 200 ppm 8 hours.
	ACGIH TLV (United States, 6/2013). STEL: 53 mg/m ³ 15 minutes. STEL: 15 ppm 15 minutes.
	TWA: 35 mg/m ³ 8 hours. TWA: 10 ppm 8 hours.
	ACGIH TLV (United States, 6/2013). TWA: 0.025 mg/m ³ 8 hours. Form: Respirable
	OSHA PEL Z3 (United States, 2/2013). TWA: 10 MG/M3 / (%SiO ₂ +2) 8 hours. Form: Respirable TWA: 250 MPPCF / (%SiO ₂ +5) 8 hours.
	Form: Respirable
	OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours.
	ACGIH TLV (United States, 6/2013). C: 100 mg/m ³ Form: Aerosol

Key to abbreviations

Section 8. Exposure controls/personal protection

A	= Acceptable Maximum Peak	S	= Potential skin absorption
ACGIH	= American Conference of Governmental Industrial Hygienists.	SR	= Respiratory sensitization
C	= Ceiling Limit	SS	= Skin sensitization
F	= Fume	STEL	= Short term Exposure limit values
IPEL	= Internal Permissible Exposure Limit	TD	= Total dust
OSHA	= Occupational Safety and Health Administration.	TLV	= Threshold Limit Value
R	= Respirable	TWA	= Time Weighted Average
Z	= OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances		

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety glasses with side shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state	: Paste
Color	: Bone
Odor	: Mild Acrylic
Odor threshold	: Not available.
pH	: 7.5-8.5
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 93.89°C (201°F)
Material supports combustion.	: Yes.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Evaporation rate	: 0.33 (butyl acetate = 1)
Vapor pressure	: 2.3 kPa (17.1 mm Hg) [room temperature]
Vapor density	: Not available.
Relative density	: 1.68
Density (lbs / gal)	: 14.02
Solubility	: Soluble in water
Partition coefficient: n-octanol/water	: Not available.
Viscosity	: 15-40 g/s
Volatility	: 29% (v/v), 17.1% (w/w)
% Solid. (w/w)	: 82.9

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Section 10. Stability and reactivity

Hazardous decomposition products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Titanium Dioxide	LD50 Oral	Rat	>10 g/kg	-
Acetaldehyde	LC50 Inhalation Gas.	Rat	13300 ppm	4 hours
	LD50 Dermal	Rabbit	3540 mg/kg	-
	LD50 Oral	Rat	661 mg/kg	-
Ethylene Glycol	LD50 Dermal	Rabbit	9.53 g/kg	-
	LD50 Oral	Rat	4700 mg/kg	-
Vinyl Acetate	LC50 Inhalation Vapor	Mouse	1460 ppm	4 hours
	LC50 Inhalation Vapor	Rat	11400 mg/m ³	4 hours
	LC50 Inhalation Vapor	Rat	3680 ppm	4 hours
	LD50 Dermal	Rabbit	2335 mg/kg	-
	LD50 Oral	Rat	2.5 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitization

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-
Acetaldehyde	-	1	Reasonably anticipated to be a human carcinogen.
Vinyl Acetate	-	2B	-
Crystalline Silica, respirable powder (<10 microns)	-	1	Known to be a human carcinogen.

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen **OSHA:** +

Not listed/not regulated: -

Section 11. Toxicological information

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category
Acetaldehyde	Category 3
Vinyl Acetate	Category 3

Specific target organ toxicity (repeated exposure)

Name	Category
Vinyl Acetate	Category 1
Crystalline Silica, respirable powder (<10 microns)	Category 2
Ethylene Glycol	Category 2

Target organs : Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, eyes.

Aspiration hazard

Not available.

Information on the likely routes of exposure Potential

acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

- Potential immediate effects** : There are no data available on the mixture itself.
- Potential delayed effects** : There are no data available on the mixture itself.

Long term exposure

- Potential immediate effects** : There are no data available on the mixture itself.
- Potential delayed effects** : There are no data available on the mixture itself.

Section 11. Toxicological information

Potential chronic health effects

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	13704.4 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute EC50 100 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Vinyl Acetate	Acute LC50 31080 to 36630 µg/l Fresh water	Fish - Poecilia reticulata	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Acetaldehyde	-0.34	-	low
Vinyl Acetate	0.73	-	low
Ethylene Glycol	-1.36	-	low

Mobility in soil

- Soil/water partition coefficient (K_{oc})** : Not available.

Section 13. Disposal considerations

- Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a

Product code KM-01009

Date of issue 4-24-2018

Version 1

Product name KM50 BONE 10.1OZ SILICONIZED ACRYLIC

Section 13. Disposal considerations

safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: **HANDLING AND STORAGE** and Section 8: **EXPOSURE CONTROLS/PERSONAL PROTECTION** for additional handling information and protection of employees. Section 6. **Accidental release measures**

14. Transport information

	DOT	IMDG	IATA
UN number	UN3082	Not regulated.	Not regulated.
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (carbendazim (ISO))	-	-
Transport hazard class (es)	9	-	-
Packing group	III	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.
Product RQ (lbs)	25000	Not applicable.	Not applicable.
RQ substances	(carbendazim (ISO))	Not applicable.	Not applicable.

Additional information

DOT : Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

IMDG : None identified.

IATA : None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States inventory (TSCA 8b) : All components are listed or exempted.

Australia inventory (AICS) : Not determined.

Canada inventory (DSL) : All components listed or exempted

China inventory (IECSC) : Not determined.

Europe inventory (REACH) : Please contact your supplier for information on the inventory status of this material.

Japan inventory (ENCS) : Not determined.

Section 15. Regulatory information

Korea inventory (KECI) : Not determined.

New Zealand (NZIoC) : Not determined.

Philippines inventory (PICCS) : Not determined.

United States

SARA 302/304

SARA 304 RQ : 711338.7 lbs / 322947.8 kg [50855.5 gal / 192509.2 L]

Composition/information on ingredients

Name	EHS	SARA 302 TPQ		SARA 304 RQ	
		(lbs)	(gallons)	(lbs)	(gallons)
Vinyl Acetate	Yes.	1000	129	5000	644.8

SARA311/312

Classification : Delayed (chronic) health hazard

Composition/information on ingredients

Name	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Titanium Dioxide	No.	No.	No.	No.	Yes.
Acetaldehyde	Yes.	No.	No.	Yes.	Yes.
Vinyl Acetate	Yes.	No.	Yes.	Yes.	Yes.
Ethylene Glycol	No.	No.	No.	Yes.	Yes.
Crystalline Silica, respirable powder (<10 microns)	No.	No.	No.	No.	Yes.

Pennsylvania (worker and community right to know act): The following components are cited in the Pennsylvania Hazardous Substances List, and are present at levels that require reporting.

Ethylene Glycol 107-21-1 <2%

SARA 313

	<u>Chemical name</u>	<u>CAS number</u>	<u>Concentration</u>
Supplier notification :	Acetaldehyde	75-07-0	0.1 - 1
	Vinyl Acetate	108-05-4	0.1 - 1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

California Prop. 65

WARNING: This product contains trace amounts of components known to the state of California to cause cancer, birth defects, or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 2 * **Flammability** : 1 **Physical hazards** : 0

Product code KM-01009	Date of issue 4-24-2018	Version 1
Product name KM50 BONE 10.1OZ SILICONIZED ACRYLIC		
Section 16. Other information		

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health : 2 **Flammability :** 1 **Instability :** 0

Date of previous issue : No previous validation.

Organization that prepared the MSDS : EHS

Key to abbreviations : ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 UN = United Nations

✔ **Indicates information that has changed from previously issued version.**

Disclaimer

The information contained herein relates only to the specific material identified. Tower Sealants believes that such information is accurate and reliable as of the date of this SDS sheet, but no representation, guarantee or warranty, expressed or implied, is made as to the accuracy, reliability, or completeness of the information. Tower Sealants urges persons receiving this information to make their own determination as to the information's suitability and completeness to their particular application. It is the buyer's / users responsibility to ensure that all activities comply with the appropriate federal, state, and local laws.