

Product Description

KM30 PAINTER'S ACRYLIC Siliconized Acrylic Caulk is a quality painter's caulk for interior and exterior use. **KM30** provides excellent adhesion to wood, drywall, plastic, metal, masonry, glass, PVC, vinyl siding and more. **KM30** is ideal for a variety of applications, including door casings & jambs, baseboards, window frames, vents, siding joints, pipe openings, eaves, moldings and trim. Meets ASTM C-834. Cured bead is mold & mildew resistant.

Performance Features

- Pro's Choice
- Siliconized Acrylic
- Cured Bead Mildew Resistant
- Paintable
- Interior / Exterior

Compliance & Performance Certifications

- Meets ASTM C-834, Type OP, Grade -0°C

Product Specifications

Color:	White
Vehicle:	Siliconized acrylic
VOC Less water and exempts solvents:	< 1.5%
Solids:	Approx. 87%
Weight per gallon:	13.9 ± 0.5
Service temperature:	-25°F to 180°F
Temperature application range:	40°F minimum and rising. 140°F maximum.
Freeze thaw stability:	Passes 5 cycles @ 0°F (1 cycle = 16 hrs. @ 0°F 8 hrs. at 75°F)
Applications:	Interior / exterior
Shelf life:	24 months when stored at 50°F to 80°F
Coverage:	10.1 fl. oz.: 55 liner ft. at a 3/16" bead
Tooling time:	10 to 15 minutes
Paint over time:	4 to 6 hours
Tack free time:	45 minutes
Full cure:	7-14 days

Surface Preparation

Surface to be caulked must be dry and free of all dirt, dust, oil, mildew, loose paint, old caulk or other contaminants. Only apply when sealant, surface and air temperatures are above 40°F and rising. Do not apply on surfaces that exceed 140°F, or when rain is expected.

Application

1. Cut nozzle at a 45° angle. Cured bead should be between 1/8" and 1/2". Use backer rod for gaps deeper than 1/2". 2. Smooth bead with a moistened cloth. 3. Clean up tools with soap and water. 4. Allow 4 to 6 hours curing time before applying paint. Coverage: 55 linear feet for a 3/16" bead. NOT INTENDED FOR AREAS THAT WILL BE SUBMERGED IN WATER. KEEP FROM FREEZING. NOT FOR FOOD CONTACT SURFACES.

Continued Next Page

KM30 PAINTER'S ACRYLIC - (cont.)

Clean Up

Clean all equipment immediately after use with warm, soapy water.

Precautions

WARNING! IRRITATING TO SKIN, EYES AND RESPIRATORY TRACT. Harmful if swallowed, inhaled or absorbed through the skin. May cause allergic skin reactions and/or central nervous system depression. Adverse reproduction effects have been reported in animals. May cause adverse kidney effects. Avoid contact with eyes, skin and clothing. Use in well ventilated area. Wear eye, skin and respiratory protection. Eye contact: Immediately flush with water for 15 minutes and get medical attention immediately. If swallowed: Do not induce vomiting. Give large quantities of water and get medical attention. Never give anything by mouth to an unconscious person. For health information refer to Material Safety Data Sheet or call Chemtrec at 800-424-9300. **KEEP OUT OF REACH OF CHILDREN.**

⚠ **WARNING:** Cancer and Reproductive Harm - Go to www.P65Warnings.ca.gov for additional information
Material Safety Data Sheets (SDS) available upon request. Similar information for solvents and other chemicals used with Kelly-Moore products should be obtained from your supplier(s). When solvents are used, proper safety precautions must be observed.

FIRST AID: In case of skin contact, wash off quickly with plenty of soap and water, remove contaminated clothing. For eye contact flush eyes immediately with large quantities of water, for at least 15 minutes. Obtain emergency medical treatment. If swallowed, obtain medical treatment immediately. **DO NOT INDUCE VOMITING.** If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help.

Proper Disposal

Contact your local sanitation department or household hazardous waste coordinator for information concerning possible reuse or disposal of unused solvent-containing adhesives and / or sealants. All material must be disposed in accordance with Federal, State, and Local Regulations.

Durability Guarantee: After proper storage and application, if this product cracks, peels or separates within 30 years of installation, manufacturer will replace the product if purchaser returns proof of purchase to manufacturer. This shall be manufacturer's sole obligation with regard to this product and manufacturer shall not be liable for any damages, including incidental or consequential damages. This is the sole and exclusive remedy and liability for defects or failure of this product. **MANUFACTURER HEREBY DISCLAIMS ALL WARRANTIES, WRITTEN OR ORAL, STATUTORY, EXPRESSED OR IMPLIED; INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS.**